

屋内照明器具特性

品番 (品名)	LGB72521		
光源	LED3500_70_1379 x1	1379.0 lm	
管理番号	K0164025(2)DB1		
BZ分類	BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	85	79	76	73	84	79	75	73	83	78	75	73	82	78	75	73	72	
	中 0.63	0.8	91	85	82	79	90	85	82	79	88	84	81	79	87	83	81	79	77	
	否 0.56	1.0	94	89	86	84	93	89	86	83	92	88	85	83	90	87	85	83	81	
下方投影面積	cm ²	1.25	97	93	90	87	96	92	89	87	94	91	89	87	93	90	88	86	85	
		1.5	99	95	92	90	98	95	92	90	96	93	91	89	94	92	90	89	87	
等価発光面積	cm ²	2.0	101	98	96	94	100	98	95	93	98	96	94	93	97	95	93	92	90	
		2.5	103	100	98	96	102	99	97	96	100	98	96	95	98	96	95	94	92	
取付高さ	器具間隔最大限		3.0	104	101	100	98	103	101	99	97	101	99	98	96	99	97	96	95	
	横方向 (A)	縦方向 (B)	4.0	105	103	102	100	104	102	101	100	102	100	99	98	100	99	98	97	
Hm	0.37Hm	0.37Hm	5.0	106	104	103	102	104	103	102	101	102	101	100	99	100	99	98	96	
			7.0	106	105	104	103	105	104	103	103	103	102	102	101	101	100	100	99	
			10.0	107	106	105	105	106	105	104	104	104	103	103	102	102	101	101	100	

