

屋内照明器具特性	
品番 (品名)	LGBZ1864
光源	LED6500_70_3650 x1 3650.0 lm
管理番号	K0157431(0)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	9%	床	10%				10%				10%				10%				0%				
下方光束	91%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	5.6	4.4	3.6	3.1	5.4	4.3	3.6	3.1	5.1	4.1	3.5	3.0	4.8	4.0	3.4	2.9	2.7			
	中	0.6	0.8	6.5	5.4	4.6	4.1	6.3	5.3	4.6	4.0	6.0	5.1	4.4	3.9	5.6	4.9	4.3	3.8	3.6			
	否	0.56	1.0	7.2	6.1	5.4	4.8	7.0	6.0	5.3	4.7	6.5	5.7	5.1	4.6	6.2	5.5	4.9	4.5	4.2			
			1.25	7.8	6.8	6.1	5.5	7.5	6.6	6.0	5.4	7.1	6.3	5.7	5.3	6.7	6.1	5.5	5.1	4.8			
下方投影面積	cm ²		1.5	8.1	7.3	6.6	6.0	7.9	7.1	6.5	5.9	7.5	6.8	6.2	5.8	7.0	6.5	6.0	5.6	5.2			
等価発光面積	cm ²		2.0	8.7	7.9	7.3	6.8	8.4	7.8	7.2	6.7	8.0	7.4	6.9	6.5	7.6	7.1	6.7	6.3	5.9			
取付高さ	器具間隔最大限		2.5	9.0	8.4	7.8	7.4	8.8	8.2	7.7	7.3	8.3	7.8	7.4	7.0	7.9	7.5	7.1	6.8	6.4			
	横方向 (A)	縦方向 (B)	3.0	9.3	8.7	8.2	7.8	9.0	8.5	8.1	7.7	8.6	8.1	7.7	7.4	8.1	7.8	7.5	7.2	6.7			
1.5m	1.85m	1.82m	4.0	9.6	9.1	8.7	8.4	9.3	8.9	8.5	8.2	8.9	8.5	8.2	7.9	8.4	8.2	7.9	7.7	7.2			
2	2.43	2.4	5.0	9.8	9.4	9.0	8.7	9.5	9.2	8.9	8.6	9.1	8.8	8.5	8.3	8.6	8.4	8.2	8.0	7.5			
2.5	2.96	2.91	7.0	10.0	9.7	9.4	9.2	9.8	9.5	9.2	9.0	9.3	9.1	8.9	8.7	8.9	8.7	8.5	8.4	7.9			
3	3.55	3.49	10.0	10.2	10.0	9.8	9.6	9.9	9.7	9.6	9.4	9.5	9.3	9.2	9.0	9.1	8.9	8.8	8.7	8.2			

