

屋内照明器具特性

品番 (品名)	LGB72702				
光源	LED5000_70_483	x1	483.0	lm	
管理番号	K0140469(0)DB1				
BZ分類	BZ5				

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		4%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		96%		壁	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.69	0.6	55	43	35	30	54	42	35	29	51	41	34	29	48	39	33	29	26	
	中	0.67	0.8	65	54	46	40	64	53	45	40	60	51	44	39	57	49	43	38	36	
	否	0.63	1.0	72	61	53	47	70	60	52	47	66	58	51	46	63	56	50	45	43	
			1.25	78	68	60	55	76	67	60	54	72	64	58	53	69	62	57	52	49	
下方投影面積	cm ²		1.5	82	73	66	60	80	72	65	60	76	69	63	59	73	67	62	58	54	
	等価発光面積		cm ²	2.0	88	80	74	69	86	79	73	68	82	76	71	67	78	73	69	65	62
取付高さ	器具間隔最大限		2.5	91	85	79	74	89	83	78	74	85	80	76	72	82	78	74	70	67	
	横方向 (A)	縦方向 (B)	3.0	94	88	83	79	92	86	82	78	88	83	80	76	84	81	77	74	71	
Hm	1.29Hm	1.29Hm	4.0	97	92	88	85	95	91	87	84	91	88	84	82	88	85	82	80	76	
			5.0	99	95	92	88	97	93	90	87	93	90	88	85	90	87	85	83	79	
			7.0	101	98	96	93	99	97	94	92	96	94	91	89	92	91	89	87	83	
			10.0	103	101	99	97	101	99	97	96	98	96	94	93	94	93	92	90	86	

