

屋内照明器具特性

品番 (品名)	LGBZ2418									
光源	LED6200_70_4899 x1 4899.0 lm									
管理番号	K0155154(0)DB1									
BZ分類	BZ6/0.7/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	7%	床	10%				10%				10%				10%				0%	
下方光束	93%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	53	41	33	27	52	40	32	27	49	38	31	26	46	37	30	26	23
	中	0.6	0.8	63	51	43	37	61	50	42	37	58	48	41	36	54	46	40	35	32
	否	0.56	1.0	70	58	50	44	68	57	49	44	64	55	48	43	60	52	47	42	39
			1.25	76	65	58	51	74	64	57	51	69	61	55	50	66	59	53	49	45
下方投影面積	cm ²		1.5	80	70	63	57	78	69	62	56	73	66	60	55	70	63	58	54	50
等価発光面積	cm ²		2.0	86	78	71	65	83	76	70	65	79	73	67	63	75	70	65	61	58
取付高さ	器具間隔最大限		2.5	89	82	76	71	87	81	75	70	83	77	73	68	79	74	70	67	63
	横方向 (A)	縦方向 (B)	3.0	92	86	80	76	90	84	79	75	85	81	76	73	81	77	74	70	66
Hm	1.36Hm	1.36Hm	4.0	95	90	86	82	93	88	84	81	89	85	81	78	85	82	79	76	72
			5.0	97	93	89	86	95	91	88	84	91	88	85	82	87	84	82	79	75
			7.0	100	97	94	91	98	95	92	89	94	91	89	87	90	88	86	84	79
			10.0	102	99	97	95	100	97	95	93	96	94	92	90	92	90	89	87	83

