

屋内照明器具特性

品番 (品名)	LGBZ2605															
光源	LED6200_70_4650 x1 4650.0 lm															
管理番号	K0156911(0)DB1															
BZ分類	BZ6/0.7/BZ5															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	5%	室指数	照明率 (X0.01)																ZCM		
下方光束	95%																				
保守率	良	0.63	0.6	54	41	33	27	52	40	33	27	49	39	32	27	46	37	31	26	24	
	中	0.6	0.8	64	51	43	37	62	50	43	37	58	49	42	36	55	47	40	36	33	
	否	0.56	1.0	70	59	51	44	68	58	50	44	64	55	49	43	61	53	47	43	40	
			1.25	76	66	58	52	74	64	57	51	70	62	55	50	67	60	54	49	46	
下方投影面積			1.5	80	71	63	57	78	69	62	57	74	67	61	56	70	64	59	55	51	
			2.0	86	78	71	66	84	76	70	65	80	74	68	64	76	71	66	62	59	
取付高さ	器具間隔最大限		2.5	90	83	77	72	88	81	76	71	84	78	73	69	80	75	71	68	64	
	横方向 (A)	縦方向 (B)	3.0	92	86	81	76	90	85	80	75	86	81	77	73	82	78	75	72	68	
Hm	1.35Hm	1.35Hm	4.0	96	91	86	82	94	89	85	81	90	86	82	79	86	83	80	77	73	
			5.0	98	94	90	86	96	92	88	85	92	89	86	83	88	85	83	81	77	
			7.0	100	97	94	91	98	95	92	90	94	92	90	87	91	89	87	85	81	
			10.0	102	100	97	95	100	98	96	94	97	95	93	91	93	91	90	89	84	

