

# 屋内照明器具特性

品番 (品名)	LGBZ4189									
光源	LED6200_70_6099 x1 6099.0lm									
管理番号	K0181800(0)DR1									
BZ分類	BZ6/0.7/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		25%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		75%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 ) ZCM																				
保守率	良	0.63	0.6	51	39	31	26	49	37	30	25	44	34	28	24	39	32	26	22	19	
	中	0.6	0.8	60	49	41	35	57	47	39	34	52	43	37	32	47	39	34	30	25	
	否	0.56	1.0	67	56	48	42	63	53	46	40	57	49	43	38	51	45	40	35	30	
			1.25	73	62	55	49	69	60	53	47	62	55	49	44	56	50	45	41	35	
下方投影面積	c m <sup>2</sup>		1.5	77	67	60	54	73	64	58	52	66	59	54	49	60	54	49	46	39	
	等価発光面積		c m <sup>2</sup>	2.0	82	74	68	62	78	71	65	60	71	65	60	56	64	60	56	52	45
取付高さ	器具間隔最大限		2.5	86	79	73	68	82	76	70	66	74	69	65	61	68	64	60	57	49	
	横方向 (A)	縦方向 (B)	3.0	88	82	77	72	84	79	74	70	77	72	69	65	70	66	63	60	53	
1.5m	2.01m	1.96m	4.0	92	87	82	78	88	83	79	76	80	77	73	70	73	70	68	65	57	
2	2.64	2.57	5.0	94	90	86	82	90	86	83	79	82	79	76	74	75	73	70	68	60	
2.5	3.3	3.21	7.0	96	93	90	87	92	89	87	84	85	82	80	78	77	76	74	72	63	
3	3.92	3.82	10.0	98	96	93	91	94	92	90	88	87	85	83	82	79	78	77	75	66	

