

屋内照明器具特性

品番 (品名)	LGC20110									
光源	LED6200_70_3699 x1					3699.0 lm				
管理番号	K0159048(0)DB1									
BZ分類	BZ4/1.1/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束 6%		反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
				床	10%				10%				10%				10%				0%		
下方光束 94%	室指数	照明率 (X0.01)																			ZCM		
保守率	良	0.63	0.6	0.6	0.56	0.6	58	46	39	34	56	46	38	34	54	44	38	33	51	43	37	33	30
	中	0.6	0.6	0.6	0.6	0.8	67	56	49	43	65	55	48	43	62	53	47	42	59	51	46	42	39
	否	0.56	0.56	0.56	0.56	1.0	73	63	56	50	71	62	55	50	68	60	54	49	64	58	52	48	45
						1.25	79	70	62	57	77	68	62	56	73	66	60	55	69	63	58	54	51
下方投影面積			cm ²		1.5	83	74	67	62	81	73	66	61	77	70	65	60	73	67	63	59	55	
	等価発光面積		cm ²		2.0	88	81	75	70	86	79	74	69	82	76	71	67	78	73	69	66	62	
取付高さ	器具間隔最大限				2.5	91	85	80	75	89	83	78	74	85	80	76	72	81	77	74	70	67	
	横方向 (A)		縦方向 (B)		3.0	94	88	83	79	91	86	82	78	87	83	79	76	84	80	77	74	70	
Hm	1.07Hm	1.09Hm		4.0	97	92	88	85	95	90	87	83	90	87	84	81	87	84	81	79	75		
				5.0	99	95	91	88	96	93	90	87	92	89	87	84	89	86	84	82	78		
				7.0	101	98	95	93	99	96	94	91	95	92	90	88	91	89	87	86	81		
				10.0	102	100	98	96	100	98	97	95	97	95	93	92	93	91	90	89	84		

