

屋内照明器具特性

品番 (品名)	LGC31126														
光源	LED6200_70_3800 x1 3800.0 lm														
管理番号	K0168483(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	8%	室指数																			
下方光束	92%	照明率 (X0.01)																			
保守率	良 0.63 中 0.6 否 0.56	0.6	5.4	4.2	3.4	2.8	5.2	4.1	3.3	2.8	4.9	3.9	3.2	2.7	4.6	3.7	3.1	2.7	2.4		
		0.8	6.4	5.2	4.4	3.8	6.2	5.1	4.3	3.7	5.8	4.8	4.2	3.7	5.4	4.6	4.0	3.6	3.3		
下方投影面積	c m ²	1.25	7.6	6.6	5.8	5.2	7.4	6.4	5.7	5.2	7.0	6.2	5.5	5.0	6.6	5.9	5.3	4.9	4.6		
		1.5	8.0	7.1	6.4	5.8	7.8	6.9	6.2	5.7	7.3	6.6	6.0	5.6	6.9	6.3	5.8	5.4	5.0		
等価発光面積	c m ²	2.0	8.6	7.8	7.2	6.6	8.4	7.6	7.0	6.5	7.9	7.3	6.8	6.3	7.5	7.0	6.5	6.2	5.8		
		2.5	9.0	8.3	7.7	7.2	8.7	8.1	7.5	7.1	8.3	7.7	7.3	6.9	7.8	7.4	7.0	6.7	6.2		
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
H m	1.30 H m	1.30 H m	4.0	9.5	9.0	8.6	8.2	9.3	8.9	8.5	8.1	8.9	8.5	8.1	7.8	8.4	8.1	7.8	7.6	7.1	
			5.0	9.7	9.3	9.0	8.6	9.5	9.1	8.8	8.5	9.1	8.7	8.5	8.2	8.6	8.4	8.1	7.9	7.5	
			7.0	10.0	9.7	9.4	9.1	9.8	9.5	9.2	8.9	9.3	9.1	8.9	8.6	8.9	8.7	8.5	8.3	7.9	
			10.0	10.2	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.5	9.3	9.2	9.0	9.1	9.0	8.8	8.7	8.2	

