

# 屋内照明器具特性

|         |                   |          |
|---------|-------------------|----------|
| 品番 (品名) | LGB77011          |          |
| 光源      | LED2700_70_467 ×1 | 467.0 lm |
| 管理番号    | K0149295(0)DB1    |          |
| BZ分類    | BZ1               |          |

| 器具効率   | 100%            | 天井      | 80%  |             |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0% |
|--------|-----------------|---------|------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
|        |                 |         | 70   | 50          | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  |    |
| 上方光束   | 0%              | 反射率     | 10%  |             |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
| 下方光束   | 100%            |         | 室指数  | 照明率 (X0.01) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |
| 保守率    | 良 0.67          | 0.6     | 84   | 77          | 73  | 71  | 83  | 77  | 73  | 71  | 82  | 76  | 73  | 71  | 80  | 76  | 73  | 70  | 69 |
|        | 中 0.63          | 0.8     | 90   | 84          | 80  | 78  | 89  | 84  | 80  | 77  | 87  | 83  | 80  | 77  | 86  | 82  | 79  | 77  | 76 |
|        | 否 0.56          | 1.0     | 93   | 88          | 85  | 82  | 92  | 88  | 85  | 82  | 91  | 87  | 84  | 82  | 89  | 86  | 83  | 81  | 80 |
| 下方投影面積 | cm <sup>2</sup> | 1.25    | 96   | 92          | 89  | 86  | 95  | 92  | 88  | 86  | 94  | 90  | 88  | 86  | 92  | 89  | 87  | 85  | 84 |
|        |                 | 1.5     | 98   | 95          | 92  | 89  | 97  | 94  | 91  | 89  | 96  | 93  | 90  | 88  | 94  | 91  | 89  | 88  | 86 |
| 等価発光面積 | cm <sup>2</sup> | 2.0     | 101  | 98          | 95  | 93  | 100 | 97  | 95  | 93  | 98  | 96  | 94  | 92  | 96  | 94  | 93  | 91  | 89 |
|        |                 | 2.5     | 103  | 100         | 98  | 96  | 101 | 99  | 97  | 95  | 99  | 98  | 96  | 94  | 98  | 96  | 95  | 93  | 91 |
| 取付高さ   | 器具間隔最大限         |         | 3.0  | 104         | 101 | 99  | 98  | 102 | 100 | 99  | 97  | 100 | 99  | 97  | 96  | 99  | 97  | 96  | 93 |
|        | 横方向 (A)         | 縦方向 (B) | 4.0  | 105         | 103 | 101 | 100 | 104 | 102 | 101 | 99  | 102 | 100 | 99  | 98  | 100 | 99  | 98  | 94 |
| Hm     | 0.46Hm          | 0.46Hm  | 5.0  | 106         | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 96 |
|        |                 |         | 7.0  | 106         | 105 | 104 | 103 | 105 | 104 | 103 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 100 | 97 |
|        |                 |         | 10.0 | 107         | 106 | 106 | 105 | 106 | 105 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 98 |

