

# 屋内照明器具特性

品番 (品名)	LGC45811														
光源	LED6200_70_4300 x1 4300.0 lm														
管理番号	K0157934(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	8%	室指数	照明率 ( X0.01 ) ZCM																		
下方光束	92%																				
保守率	良 0.63 中 0.6 否 0.56	0.6	55	43	35	29	53	42	34	29	50	40	33	28	47	38	32	28	26		
		0.8	65	53	45	39	63	52	44	39	59	50	43	38	56	48	42	37	34		
		1.0	71	60	52	46	69	59	51	46	65	56	50	45	61	54	48	44	41		
		1.25	77	67	59	54	75	66	58	53	71	63	57	52	67	60	55	51	47		
下方投影面積	c m <sup>2</sup>	1.5	81	72	65	59	79	70	64	58	74	67	62	57	71	65	60	55	52		
		2.0	87	79	73	67	84	77	71	66	80	74	69	65	76	71	67	63	59		
等価発光面積	c m <sup>2</sup>	2.5	90	83	78	73	88	82	76	72	83	78	74	70	79	75	71	68	64		
		3.0	93	87	82	77	90	85	80	76	86	82	78	74	82	78	75	72	68		
取付高さ	器具間隔最大限		4.0	96	91	87	83	94	89	85	82	89	86	82	79	85	82	80	77	73	
	横方向 (A)	縦方向 (B)	5.0	98	94	90	87	96	92	89	86	91	88	86	83	87	85	83	80	76	
1.5m	1.92m	1.93m	7.0	100	97	94	92	98	95	93	90	94	92	89	87	90	88	86	85	80	
2	2.53	2.55	10.0	102	100	98	96	100	98	96	94	96	94	92	91	92	91	89	88	83	
2.5	3.09	3.11																			
3	3.7	3.73																			

