

# 屋内照明器具特性

品番 (品名) **LGB78230**

光源 LED5000\_70\_497 ×1 497.0 lm

管理番号 K0161900(0)DB1

BZ分類 BZ1

| 器具効率             | 100%            | 天井      | 80%          |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
|------------------|-----------------|---------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
|                  |                 |         | 70           | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  |     |    |
| 上方光束             | 0%              | 反射率     | 壁            | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
| 下方光束             | 100%            |         | 床            | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
|                  |                 | 室指数     | 照明率 ( X0.01) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率              | 良 0.67          | 0.6     | 85           | 80  | 76  | 73  | 85  | 79  | 76  | 73  | 83  | 79  | 75  | 73  | 82  | 78  | 75  | 73  | 72  |    |
|                  | 中 0.63          | 0.8     | 91           | 86  | 83  | 80  | 91  | 86  | 83  | 80  | 89  | 85  | 82  | 80  | 88  | 84  | 82  | 80  | 79  |    |
|                  | 否 0.56          | 1.0     | 95           | 90  | 87  | 85  | 94  | 90  | 87  | 85  | 92  | 89  | 86  | 84  | 91  | 88  | 86  | 84  | 83  |    |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> | 1.25    | 98           | 94  | 91  | 89  | 97  | 93  | 91  | 88  | 95  | 92  | 90  | 88  | 94  | 91  | 89  | 87  | 86  |    |
|                  |                 | 1.5     | 100          | 96  | 93  | 91  | 99  | 95  | 93  | 91  | 97  | 94  | 92  | 90  | 95  | 93  | 91  | 90  | 88  |    |
|                  |                 | 2.0     | 102          | 99  | 97  | 95  | 101 | 98  | 96  | 94  | 99  | 97  | 95  | 94  | 97  | 96  | 94  | 93  | 91  |    |
| 取付高さ             | 器具間隔最大限         |         | 2.5          | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 97  | 100 | 98  | 97  | 96  | 98  | 97  | 96  | 95  | 93 |
|                  | 横方向 (A)         | 縦方向 (B) | 3.0          | 104 | 102 | 100 | 99  | 103 | 101 | 100 | 98  | 101 | 100 | 98  | 97  | 99  | 98  | 97  | 96  | 94 |
| Hm               | 0.65Hm          | 0.65Hm  | 4.0          | 105 | 104 | 102 | 101 | 104 | 103 | 101 | 100 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 98  | 95 |
|                  |                 |         | 5.0          | 106 | 105 | 103 | 102 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 101 | 100 | 99  | 99  | 96 |
|                  |                 |         | 7.0          | 107 | 106 | 105 | 104 | 106 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 100 | 100 | 100 | 97 |
|                  |                 |         | 10.0         | 107 | 107 | 106 | 105 | 106 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 101 | 101 | 98 |

