

# 屋内照明器具特性

品番 (品名)	LGC45810															
光源	LED6500_70_4850 x1 4850.0 lm															
管理番号	K0138131(0)DB1															
BZ分類	BZ5															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	11%	室指数																			
下方光束	89%	照明率 ( X0.01)																			
保守率	良 0.63 中 0.6 否 0.56	ZCM																			
		0.6	54	42	34	29	52	41	34	28	49	39	32	28	46	37	31	27	24		
下方投影面積	c m <sup>2</sup>	1.25	76	66	59	53	74	64	57	52	69	61	55	50	64	58	53	49	45		
		1.5	80	71	64	58	78	69	62	57	73	66	60	55	68	62	57	53	49		
等価発光面積	c m <sup>2</sup>	2.0	86	78	71	66	83	76	70	65	78	72	67	63	73	68	64	61	56		
		2.5	89	82	77	72	87	80	75	71	81	76	72	68	77	72	69	65	61		
取付高さ	器具間隔最大限		3.0																		
	横方向 (A)	縦方向 (B)	3.0	92	86	81	76	89	84	79	75	84	79	75	72	79	75	72	69	64	
1.5m	1.96m	1.96m	4.0	95	90	86	82	92	88	84	80	87	84	80	77	82	79	77	74	69	
2	2.57	2.58	5.0	97	93	89	86	94	91	87	84	89	86	83	81	84	82	80	77	72	
2.5	3.19	3.2	7.0	99	96	93	91	97	94	91	89	92	89	87	85	87	85	83	82	76	
3	3.76	3.77	10.0	101	99	97	95	98	96	94	93	94	92	90	89	89	88	86	85	79	

