

# 屋内照明器具特性

品番 (品名)	LGC55804														
光源	LED6500_70_4850 x1 4850.0 1 m														
管理番号	K0139562(0)DB1														
BZ分類	BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	10 %	室指数	照明率 ( X0.01 )																ZCM		
下方光束	90 %																				
保守率	良	0.63	0.6	54	41	33	28	52	40	33	27	48	38	32	27	45	37	31	26	23	
	中	0.6	0.8	63	51	43	37	61	50	43	37	57	48	41	36	53	45	40	35	32	
	否	0.56	1.0	70	59	51	44	67	57	50	44	63	54	48	43	59	52	46	41	38	
			1.25	76	65	58	52	73	64	57	51	69	61	54	49	64	58	52	48	44	
下方投影面積			1.5	80	70	63	57	77	69	62	56	72	65	59	55	68	62	57	53	49	
			2.0	85	77	71	65	83	76	69	64	78	72	67	62	73	68	64	60	56	
取付高さ	器具間隔最大限		2.5	89	82	76	71	86	80	75	70	82	76	72	68	77	73	69	65	61	
	横方向 (A)	縦方向 (B)	3.0	92	85	80	76	89	83	79	74	84	79	75	72	79	76	72	69	64	
1.5m	1.97 m	1.96 m	4.0	95	90	86	82	92	88	84	80	87	84	80	77	83	80	77	74	69	
2	2.59	2.58	5.0	97	93	89	86	94	91	87	84	90	86	84	81	85	82	80	78	73	
2.5	3.24	3.22	7.0	99	96	93	91	97	94	91	89	92	90	87	85	88	86	84	82	77	
3	3.84	3.83	10.0	101	99	97	95	99	97	95	93	94	92	91	89	90	88	87	85	80	

