

| 屋内照明器具特性 | |
|----------|-----------------------------|
| 品番 (品名) | LGD3113 |
| 光源 | LED2700_70_485 x1 485.0 l m |
| 管理番号 | K0149219 (0) DB 1 |
| BZ分類 | BZ3 / 8.5 / BZ2 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|----------|----------|---------------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|----|----|-----|----|
| 器具効率 | 100 % | 天井 | 80 % | | | | 70 % | | | | 50 % | | | | 30 % | | | | 0 % | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0 % | |
| 上方光束 | 0 % | 床 | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | 0 % | |
| 下方光束 | 100 % | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.67 | 0.6 | 62 | 51 | 44 | 39 | 61 | 50 | 44 | 39 | 59 | 49 | 43 | 39 | 57 | 49 | 43 | 39 | 37 |
| | 中 | 0.63 | 0.8 | 73 | 63 | 56 | 51 | 71 | 62 | 56 | 51 | 69 | 61 | 55 | 51 | 67 | 60 | 55 | 50 | 49 |
| | 否 | 0.56 | 1.0 | 80 | 71 | 64 | 60 | 78 | 70 | 64 | 59 | 76 | 69 | 63 | 59 | 73 | 67 | 62 | 59 | 57 |
| | | | 1.25 | 86 | 78 | 72 | 67 | 84 | 77 | 71 | 67 | 82 | 75 | 71 | 67 | 79 | 74 | 70 | 66 | 64 |
| 下方投影面積 | | | 1.5 | 89 | 82 | 77 | 73 | 88 | 82 | 77 | 72 | 85 | 80 | 75 | 72 | 83 | 78 | 74 | 71 | 69 |
| | | | 2.0 | 94 | 89 | 84 | 80 | 93 | 88 | 84 | 80 | 90 | 86 | 82 | 79 | 88 | 84 | 81 | 78 | 76 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 97 | 93 | 89 | 85 | 96 | 92 | 88 | 85 | 93 | 90 | 87 | 84 | 91 | 88 | 85 | 83 | 81 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 99 | 95 | 92 | 89 | 98 | 94 | 91 | 88 | 95 | 92 | 89 | 87 | 93 | 90 | 88 | 86 | 84 |
| H m | 1.24 H m | 1.24 H m | 4.0 | 101 | 98 | 96 | 93 | 100 | 97 | 95 | 92 | 98 | 95 | 93 | 91 | 95 | 93 | 92 | 90 | 87 |
| | | | 5.0 | 103 | 100 | 98 | 96 | 102 | 99 | 97 | 95 | 99 | 97 | 95 | 94 | 97 | 95 | 94 | 92 | 90 |
| | | | 7.0 | 104 | 103 | 101 | 99 | 103 | 101 | 100 | 98 | 101 | 99 | 98 | 97 | 98 | 97 | 96 | 95 | 93 |
| | | | 10.0 | 106 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99 | 100 | 99 | 98 | 97 | 95 |

