

屋内照明器具特性

品番 (品名)	LGD1131	
光源	LED2700_70_467 ×1	467.0 lm
管理番号	K0149295(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	
上方光束	0%	反射率	壁	10%				10%				10%				10%			
下方光束	100%		床	10%				10%				10%				10%			
		室指数	照明率 (X0.01)																ZCM
保守率	良 0.67	0.6	84	77	73	71	83	77	73	71	82	76	73	71	80	76	73	70	69
	中 0.63	0.8	90	84	80	78	89	84	80	77	87	83	80	77	86	82	79	77	76
	否 0.56	1.0	93	88	85	82	92	88	85	82	91	87	84	82	89	86	83	81	80
下方投影面積	cm ²	1.25	96	92	89	86	95	92	88	86	94	90	88	86	92	89	87	85	84
		1.5	98	95	92	89	97	94	91	89	96	93	90	88	94	91	89	88	86
等価発光面積	cm ²	2.0	101	98	95	93	100	97	95	93	98	96	94	92	96	94	93	91	89
		2.5	103	100	98	96	101	99	97	95	99	98	96	94	98	96	95	93	91
取付高さ	器具間隔最大限		3.0	104	101	99	98	102	100	99	97	100	99	97	96	99	97	96	93
	横方向 (A)	縦方向 (B)	4.0	105	103	101	100	104	102	101	99	102	100	99	98	100	99	98	94
Hm	0.46Hm	0.46Hm	5.0	106	104	103	102	104	103	102	101	102	101	100	99	100	99	98	96
			7.0	106	105	104	103	105	104	103	103	103	102	102	101	101	100	99	97
			10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	98

