

# 屋内照明器具特性

品番 (品名)	NNN17711K+NNN89990	
光源	LED4000_80_7355 x1 7355.0 lm	
管理番号	K0150647(0)DB1	
BZ分類	BZ1/2.3/BZ2	

器具効率	100%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	4%	床	10%				10%				10%				10%				0%			
下方光束	96%	室指数	照明率 (X0.01) ZCM																			
保守率	良 中 否 0.76 0.72 0.64	0.6	74	66	61	58	73	66	61	57	71	65	60	57	69	64	60	57	55			
		0.8	81	74	69	65	80	73	69	65	78	72	68	65	76	71	67	64	62			
		1.0	86	79	75	71	85	79	74	71	82	77	73	70	80	75	72	69	67			
		1.25	90	84	80	76	89	83	79	76	86	81	78	75	83	80	76	74	72			
下方投影面積	c m <sup>2</sup>	1.5	93	87	83	80	91	86	82	79	88	84	81	78	86	82	79	77	75			
		2.0	96	92	88	85	95	90	87	84	92	88	85	83	89	86	84	82	79			
取付高さ	器具間隔最大限		2.5	98	94	91	88	97	93	90	88	94	91	88	86	91	89	86	85	82		
	横方向 (A)	縦方向 (B)	3.0	100	96	93	91	98	95	92	90	95	93	90	88	92	90	88	87	84		
H m	0.98 H m	0.97 H m	4.0	102	99	96	94	100	97	95	93	97	95	93	91	94	92	91	89	86		
			5.0	103	100	98	97	101	99	97	95	98	96	95	93	95	94	92	91	88	88	
			7.0	104	102	101	99	102	101	99	98	99	98	97	96	96	95	94	93	90		
			10.0	105	104	103	101	103	102	101	100	100	99	98	98	97	97	96	95	91		

