

屋内照明器具特性	
品番 (品名)	LGBZ1196
光源	LED6200_70_4299 x1 4299.0lm
管理番号	K0150722(0)DB1
BZ分類	BZ6/0.7/BZ5

器具効率	99%	天井	80%				70%				50%				30%				0%		
	上方光束		30%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	69%	床	10%				10%				10%				10%				0%		
室指数			照明率 (X0.01) ZCM																		
保守率	良	0.63	0.6	50	38	31	26	47	37	30	25	42	33	27	23	37	30	25	21	17	
	中	0.6	0.8	60	48	40	35	56	46	39	34	50	42	36	31	44	38	33	29	24	
	否	0.56	1.0	66	55	47	42	62	53	46	40	55	48	42	37	49	43	38	34	29	
			1.25	72	62	54	49	68	59	52	47	60	53	48	43	54	48	44	40	34	
下方投影面積	c m ²		1.5	76	67	60	54	72	64	57	52	64	58	52	48	57	52	48	44	37	
	等価発光面積		c m ²	2.0	81	74	67	62	77	70	65	60	69	64	59	55	62	57	54	51	43
取付高さ	器具間隔最大限		2.5	85	78	73	68	80	75	70	65	72	68	64	60	65	61	58	55	47	
	横方向 (A)	縦方向 (B)	3.0	87	81	77	72	83	78	73	69	75	70	67	64	67	64	61	58	50	
H m	1.33H m	1.33H m	4.0	90	86	82	78	86	82	78	75	78	74	71	69	70	67	65	63	54	
			5.0	92	88	85	82	88	84	81	79	79	77	74	72	72	69	68	66	56	
			7.0	95	92	89	87	90	88	85	83	82	80	78	76	74	72	71	69	59	
			10.0	96	94	92	90	92	90	88	87	83	82	81	79	75	74	73	72	62	

