

屋内照明器具特性

品番 (品名) **LGB84347**

光源 **LED5000_70_964 ×1 964.0 lm**

管理番号 **K0135903(0)DB1**

BZ分類 **BZ1**

器具効率	101%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	101%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	86	80	76	73	85	79	76	73	84	79	76	73	83	78	75	73	72	
	中 0.63	0.8	92	86	83	80	91	86	83	80	89	85	82	80	88	84	82	80	78	
	否 0.56	1.0	95	91	87	85	94	90	87	84	93	89	86	84	91	88	86	84	82	
下方投影面積	cm ²	1.25	98	94	91	89	97	93	91	88	95	92	90	88	94	91	89	87	86	
		1.5	100	96	94	91	99	96	93	91	97	94	92	90	96	93	91	90	88	
等価発光面積	cm ²	2.0	102	99	97	95	101	99	96	95	99	97	95	94	98	96	94	93	91	
		2.5	104	101	99	97	103	100	99	97	101	99	97	96	99	97	96	95	93	
取付高さ	器具間隔最大限		3.0	105	103	101	99	104	102	100	99	102	100	99	97	100	98	97	96	94
	横方向 (A)	縦方向 (B)	4.0	106	104	103	101	105	103	102	101	103	101	100	99	101	100	99	98	96
Hm	0.42Hm	0.42Hm	5.0	107	105	104	103	105	104	103	102	103	102	101	101	101	100	99	97	
			7.0	107	106	105	105	106	105	104	104	103	103	102	102	101	101	100	98	
			10.0	108	107	107	106	107	106	106	105	105	104	104	103	103	102	102	101	99

