

屋内照明器具特性

品番 (品名)	LGW40064	
光源	LED2700_70_473 ×1	473.0 lm
管理番号	K0135331(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%					
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10						
上方光束	0%	反射率	壁		床		10%		10%		10%		10%		10%		10%		0%					
下方光束	100%		室指数		照明率 (X0.01)																ZCM			
保守率	良 0.63	0.6	0.6	84	78	74	71	83	77	74	71	82	77	73	71	81	76	73	71	70				
	中 0.6	0.6	0.8	90	84	81	78	89	84	80	78	87	83	80	77	86	82	79	77	76				
	否 0.56	0.6	1.0	93	89	85	82	93	88	85	82	91	87	84	82	89	86	83	81	80				
下方投影面積	cm ²	等価発光面積	cm ²	1.25	97	92	89	86	96	92	89	86	94	90	88	86	92	89	87	85	84			
				1.5	99	95	92	89	98	94	91	89	96	93	90	88	94	92	89	88	86	86		
取付高さ	器具間隔最大限		Hm	0.43Hm	0.43Hm	2.5	103	100	98	96	102	99	97	95	100	98	96	94	98	96	93	91		
	横方向 (A)	縦方向 (B)				3.0	104	101	99	98	103	101	99	97	101	99	97	96	99	97	96	95	93	
Hm	0.43Hm	0.43Hm	Hm	0.43Hm	Hm	4.0	105	103	102	100	104	102	101	100	102	100	99	98	100	99	98	97	95	
						5.0	106	104	103	102	105	103	102	101	103	101	100	99	101	100	99	98	97	96
Hm	0.43Hm	0.43Hm	Hm	0.43Hm	Hm	7.0	107	106	105	104	106	105	104	103	103	103	102	101	101	100	99	97	97	97
						10.0	107	107	106	105	106	105	105	104	104	103	103	102	102	101	101	100	98	98

