

屋内照明器具特性

品番 (品名)	L G W 4 5 5 4 0 Y Z																
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 l m																
管理番号	K0158854(0)DB1																
BZ分類	BZ10																

器具効率	45 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	23 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	22 %		床	10 %				10 %				10 %				10 %				0 %
室指数			照明率 (X 0.01) Z C M																	
保守率	良	0.69	0.6	1.8	1.3	0.9	0.6	1.7	1.1	0.8	0.6	1.3	0.9	0.6	1.0	0.7	0.5	0.3	0.1	
	中	0.67	0.8	2.2	1.6	1.2	0.9	2.0	1.5	1.1	0.8	1.6	1.2	0.9	1.2	0.9	0.7	0.5	0.2	
	否	0.63	1.0	2.5	1.9	1.5	1.2	2.2	1.7	1.4	1.1	1.8	1.4	1.1	1.4	1.1	0.8	0.7	0.3	
			1.25	2.7	2.2	1.8	1.4	2.4	2.0	1.6	1.3	2.0	1.6	1.3	1.1	1.5	1.2	1.0	0.8	0.4
下方投影面積		cm ²	1.5	2.9	2.4	2.0	1.7	2.6	2.2	1.8	1.5	2.1	1.8	1.5	1.3	1.7	1.4	1.2	1.0	0.5
等価発光面積		cm ²	2.0	3.2	2.7	2.3	2.0	2.9	2.5	2.1	1.9	2.3	2.0	1.8	1.5	1.8	1.6	1.4	1.2	0.7
取付高さ	器具間隔最大限		2.5	3.3	2.9	2.6	2.3	3.0	2.7	2.4	2.1	2.5	2.2	2.0	1.8	2.0	1.8	1.6	1.4	0.8
	横方向 (A)	縦方向 (B)	3.0	3.4	3.1	2.8	2.5	3.2	2.8	2.6	2.3	2.6	2.3	2.1	1.9	2.1	1.9	1.7	1.5	1.0
H m	0.00 H m	0.00 H m	4.0	3.6	3.3	3.0	2.8	3.3	3.1	2.8	2.6	2.8	2.5	2.3	2.2	2.2	2.1	1.9	1.8	1.1
			5.0	3.7	3.5	3.2	3.0	3.4	3.2	3.0	2.8	2.9	2.7	2.5	2.3	2.3	2.2	2.0	1.9	1.3
			7.0	3.9	3.7	3.5	3.3	3.6	3.4	3.2	3.0	3.0	2.8	2.7	2.6	2.4	2.3	2.2	2.1	1.4
			10.0	4.0	3.8	3.7	3.5	3.7	3.5	3.4	3.3	3.1	3.0	2.9	2.8	2.6	2.5	2.4	2.3	1.6

