

| | |
|----------|--|
| 屋内照明器具特性 | |
| 品番 (品名) | L G W 5 0 6 3 2 F |
| 光源 | LDA7N- G/ E/ W ×2 810.0 l m |
| 管理番号 | K0169056 (0) DB 1 |
| B Z 分類 | B Z 6 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------------------------|-----------|---------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-------|----|
| 器具効率 | 53 % | 天井 | 80 % | | | | 70 % | | | | 50 % | | | | 30 % | | | | 0 % | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0 % | |
| 上方光束 | 8 % | 床 | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | 0 % | |
| 下方光束 | 45 % | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | Z C M | |
| 保守率 | 良 0.63 中 0.6 否 0.56 | 0.6 | 27 | 20 | 16 | 13 | 26 | 19 | 15 | 12 | 23 | 18 | 14 | 12 | 22 | 17 | 14 | 11 | 10 | |
| | | 0.8 | 32 | 25 | 21 | 17 | 30 | 24 | 20 | 17 | 28 | 23 | 19 | 16 | 26 | 21 | 18 | 16 | 14 | |
| | | 1.0 | 35 | 29 | 24 | 21 | 33 | 28 | 24 | 20 | 31 | 26 | 22 | 19 | 28 | 24 | 21 | 19 | 16 | |
| | | 1.25 | 38 | 32 | 28 | 24 | 36 | 31 | 27 | 24 | 33 | 29 | 26 | 23 | 31 | 27 | 24 | 22 | 19 | |
| 下方投影面積 | c m ² | 1.5 | 40 | 35 | 31 | 27 | 39 | 34 | 30 | 27 | 35 | 31 | 28 | 25 | 33 | 29 | 26 | 24 | 21 | |
| | | 2.0 | 43 | 38 | 35 | 31 | 41 | 37 | 34 | 31 | 38 | 35 | 32 | 29 | 35 | 32 | 30 | 28 | 25 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 45 | 41 | 38 | 35 | 43 | 40 | 36 | 34 | 40 | 37 | 34 | 32 | 37 | 35 | 32 | 30 | 27 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 47 | 43 | 40 | 37 | 45 | 41 | 39 | 36 | 42 | 39 | 36 | 34 | 39 | 36 | 34 | 32 | 29 |
| H m | 1.33 H m | 1.33 H m | 4.0 | 48 | 45 | 43 | 40 | 47 | 44 | 41 | 39 | 43 | 41 | 39 | 37 | 40 | 39 | 37 | 35 | 32 |
| | | | 5.0 | 50 | 47 | 45 | 42 | 48 | 45 | 43 | 41 | 45 | 43 | 41 | 39 | 42 | 40 | 39 | 37 | 34 |
| | | | 7.0 | 51 | 49 | 47 | 45 | 49 | 47 | 46 | 44 | 46 | 45 | 43 | 42 | 43 | 42 | 41 | 40 | 36 |
| | | | 10.0 | 52 | 51 | 49 | 48 | 50 | 49 | 48 | 46 | 47 | 46 | 45 | 44 | 44 | 43 | 43 | 42 | 38 |

