

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | LGC45808                     |
| 光源       | LED6500_70_4050 x1 4050.0 lm |
| 管理番号     | K0157520(0)DB1               |
| BZ分類     | BZ5                          |

|        |                 |         |               |      |      |     |     |      |     |     |     |     |     |     |     |     |     |     |     |     |  |  |     |
|--------|-----------------|---------|---------------|------|------|-----|-----|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|--|-----|
| 器具効率   | 100%            | 天井      | 80%           |      |      |     | 70% |      |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |  |  |     |
|        |                 | 壁       | 70            | 50   | 30   | 10  | 70  | 50   | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |     |  |  |     |
| 上方光束   | 5%              | 床       | 10%           |      |      |     | 10% |      |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |  |  |     |
| 下方光束   | 95%             | 室指数     | 照明率 ( X0.01 ) |      |      |     |     |      |     |     |     |     |     |     |     |     |     |     |     |     |  |  | ZCM |
| 保守率    | 良               | 0.63    | 0.6           | 5.4  | 4.2  | 3.4 | 2.8 | 5.3  | 4.1 | 3.3 | 2.8 | 5.0 | 3.9 | 3.2 | 2.7 | 4.7 | 3.8 | 3.2 | 2.7 | 2.5 |  |  |     |
|        | 中               | 0.6     | 0.8           | 6.4  | 5.2  | 4.4 | 3.8 | 6.2  | 5.1 | 4.3 | 3.7 | 5.9 | 4.9 | 4.2 | 3.7 | 5.6 | 4.7 | 4.1 | 3.6 | 3.4 |  |  |     |
|        | 否               | 0.56    | 1.0           | 7.0  | 5.9  | 5.1 | 4.5 | 6.8  | 5.8 | 5.0 | 4.4 | 6.5 | 5.6 | 4.9 | 4.4 | 6.1 | 5.4 | 4.8 | 4.3 | 4.0 |  |  |     |
|        |                 |         | 1.25          | 7.6  | 6.6  | 5.8 | 5.2 | 7.4  | 6.5 | 5.7 | 5.2 | 7.0 | 6.2 | 5.6 | 5.1 | 6.7 | 6.0 | 5.4 | 5.0 | 4.7 |  |  |     |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5           | 8.0  | 7.1  | 6.3 | 5.7 | 7.8  | 6.9 | 6.3 | 5.7 | 7.4 | 6.7 | 6.1 | 5.6 | 7.1 | 6.4 | 5.9 | 5.5 | 5.1 |  |  |     |
| 等価発光面積 | cm <sup>2</sup> |         | 2.0           | 8.6  | 7.8  | 7.1 | 6.6 | 8.4  | 7.6 | 7.0 | 6.5 | 8.0 | 7.4 | 6.8 | 6.4 | 7.6 | 7.1 | 6.6 | 6.2 | 5.9 |  |  |     |
| 取付高さ   | 器具間隔最大限         |         | 2.5           | 9.0  | 8.3  | 7.7 | 7.2 | 8.8  | 8.1 | 7.5 | 7.1 | 8.4 | 7.8 | 7.3 | 6.9 | 8.0 | 7.5 | 7.1 | 6.7 | 6.4 |  |  |     |
|        | 横方向 (A)         | 縦方向 (B) | 3.0           | 9.2  | 8.6  | 8.1 | 7.6 | 9.0  | 8.4 | 7.9 | 7.5 | 8.6 | 8.1 | 7.7 | 7.3 | 8.2 | 7.8 | 7.5 | 7.1 | 6.8 |  |  |     |
| 1.5m   | 2.03m           | 2.02m   | 4.0           | 9.6  | 9.0  | 8.6 | 8.2 | 9.4  | 8.9 | 8.5 | 8.1 | 9.0 | 8.6 | 8.2 | 7.9 | 8.6 | 8.3 | 8.0 | 7.7 | 7.3 |  |  |     |
| 2      | 2.67            | 2.67    | 5.0           | 9.8  | 9.3  | 8.9 | 8.6 | 9.6  | 9.2 | 8.8 | 8.5 | 9.2 | 8.8 | 8.5 | 8.2 | 8.8 | 8.5 | 8.3 | 8.0 | 7.6 |  |  |     |
| 2.5    | 3.31            | 3.31    | 7.0           | 10.0 | 9.7  | 9.4 | 9.1 | 9.8  | 9.5 | 9.2 | 9.0 | 9.4 | 9.2 | 8.9 | 8.7 | 9.1 | 8.9 | 8.7 | 8.5 | 8.1 |  |  |     |
| 3      | 3.88            | 3.87    | 10.0          | 10.2 | 10.0 | 9.7 | 9.5 | 10.0 | 9.8 | 9.6 | 9.4 | 9.6 | 9.5 | 9.3 | 9.1 | 9.3 | 9.1 | 9.0 | 8.8 | 8.4 |  |  |     |

