

屋内照明器具特性

品番 (品名)	L G W 5 1 7 1 0	
光源	LED5000_70_772 x1	772.0 l m
管理番号	K0150434 (0) DB 1	
B Z 分類	B Z 5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	2 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	98 %		室指数	照明率 (X 0.01)																Z C M
保守率	良	0.63	0.6	5.6	4.4	3.6	3.0	5.5	4.3	3.6	3.0	5.2	4.2	3.5	3.0	5.0	4.1	3.4	3.0	2.8
	中	0.6	0.8	6.6	5.4	4.6	4.1	6.4	5.3	4.6	4.0	6.1	5.2	4.5	4.0	5.9	5.0	4.4	4.0	3.7
	否	0.56	1.0	7.3	6.2	5.4	4.8	7.1	6.1	5.3	4.8	6.8	5.9	5.2	4.7	6.5	5.7	5.1	4.7	4.4
			1.25	7.8	6.9	6.1	5.5	7.7	6.7	6.0	5.5	7.3	6.5	5.9	5.4	7.0	6.4	5.8	5.4	5.1
下方投影面積	c m ²		1.5	8.3	7.4	6.6	6.1	8.1	7.2	6.6	6.0	7.7	7.0	6.4	6.0	7.4	6.8	6.3	5.9	5.6
等価発光面積	c m ²		2.0	8.8	8.1	7.4	6.9	8.6	7.9	7.4	6.9	8.3	7.7	7.2	6.8	8.0	7.5	7.0	6.7	6.4
取付高さ	器具間隔最大限		2.5	9.2	8.5	8.0	7.5	9.0	8.4	7.9	7.4	8.7	8.1	7.7	7.3	8.3	7.9	7.5	7.2	6.9
	横方向 (A)	縦方向 (B)	3.0	9.4	8.8	8.3	7.9	9.2	8.7	8.3	7.8	8.9	8.5	8.1	7.7	8.6	8.2	7.9	7.6	7.3
H m	1.28 H m	1.28 H m	4.0	9.7	9.3	8.9	8.5	9.6	9.1	8.8	8.4	9.2	8.9	8.6	8.3	8.9	8.6	8.4	8.1	7.8
			5.0	9.9	9.5	9.2	8.9	9.8	9.4	9.1	8.8	9.4	9.1	8.9	8.6	9.1	8.9	8.7	8.4	8.1
			7.0	10.2	9.9	9.6	9.3	10.0	9.7	9.5	9.2	9.7	9.5	9.3	9.1	9.4	9.2	9.0	8.9	8.5
			10.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.6	9.9	9.7	9.6	9.4	9.6	9.5	9.3	9.2	8.9

