

屋内照明器具特性	
品番 (品名)	L G W 5 0 6 2 2 F
光源	LDA4N- G/ E/ W ×2 485.0 l m
管理番号	K0168624 (0) DB 1
B Z 分類	B Z 6

器具効率	53 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	8 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	45 %	室指数	照明率 (X0.01)																Z C M	
保守率	良	0.63	0.6	27	20	16	13	26	19	15	12	24	18	15	12	22	17	14	11	10
	中	0.6	0.8	32	25	21	17	30	24	20	17	28	23	19	16	26	21	18	16	14
	否	0.56	1.0	35	29	24	21	34	28	24	20	31	26	22	19	28	24	21	19	16
			1.25	38	32	28	24	37	31	27	24	34	29	26	23	31	27	24	22	19
下方投影面積		c m ²	1.5	40	35	31	27	39	34	30	27	36	31	28	25	33	29	27	24	22
等価発光面積		c m ²	2.0	43	39	35	32	42	37	34	31	39	35	32	29	36	33	30	28	25
取付高さ	器具間隔最大限		2.5	45	41	38	35	44	40	37	34	40	37	35	32	37	35	33	31	27
	横方向 (A)	縦方向 (B)	3.0	47	43	40	37	45	42	39	36	42	39	37	34	39	36	34	33	29
H m	1.34 H m	1.34 H m	4.0	49	46	43	40	47	44	42	39	44	41	39	37	41	39	37	35	32
			5.0	50	47	45	43	48	46	44	42	45	43	41	39	42	40	39	37	34
			7.0	51	49	47	46	50	48	46	44	46	45	43	42	43	42	41	40	36
			10.0	52	51	49	48	51	49	48	47	48	46	45	44	45	44	43	42	38

