

# 屋内照明器具特性

品番 (品名)	L G W 5 0 6 3 1 F															
光源	LDA7L - G / E / W × 2                      810.0 1 m															
管理番号	K0169055 ( 0 ) DB 1															
B Z 分類	B Z 6															

器具効率	63 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	10 %																			
下方光束	53 %																			
室指数	照明率 ( X 0.01 )                      Z C M																			
保守率	良 中 否 0.63 0.6 0.56	0.6	3.2	2.4	1.9	1.5	3.0	2.3	1.8	1.5	2.8	2.2	1.7	1.4	2.6	2.0	1.6	1.4	1.2	
		0.8	3.8	3.0	2.4	2.1	3.6	2.9	2.4	2.0	3.3	2.7	2.3	1.9	3.0	2.5	2.1	1.8	1.6	
		1.0	4.2	3.4	2.9	2.5	4.0	3.3	2.8	2.4	3.7	3.1	2.6	2.3	3.4	2.9	2.5	2.2	1.9	
		1.25	4.5	3.8	3.3	2.9	4.3	3.7	3.2	2.8	4.0	3.4	3.0	2.7	3.7	3.2	2.9	2.6	2.3	
下方投影面積	c m <sup>2</sup>	1.5	4.8	4.1	3.6	3.2	4.6	4.0	3.5	3.2	4.2	3.7	3.3	3.0	3.9	3.5	3.1	2.9	2.5	
		2.0	5.1	4.6	4.1	3.7	4.9	4.4	4.0	3.7	4.6	4.1	3.8	3.5	4.2	3.9	3.6	3.3	3.0	
取付高さ	器具間隔最大限		2.5	5.4	4.9	4.5	4.1	5.2	4.7	4.3	4.0	4.8	4.4	4.1	3.8	4.4	4.1	3.9	3.6	3.2
	横方向 ( A )	縦方向 ( B )	3.0	5.5	5.1	4.7	4.4	5.3	4.9	4.6	4.3	4.9	4.6	4.3	4.1	4.6	4.3	4.1	3.9	3.5
H m	1.33 H m	1.33 H m	4.0	5.8	5.4	5.1	4.8	5.6	5.2	4.9	4.7	5.2	4.9	4.6	4.4	4.8	4.6	4.4	4.2	3.8
			5.0	5.9	5.6	5.3	5.0	5.7	5.4	5.2	4.9	5.3	5.1	4.9	4.7	4.9	4.8	4.6	4.4	4.0
			7.0	6.1	5.8	5.6	5.4	5.9	5.6	5.4	5.2	5.5	5.3	5.1	5.0	5.1	5.0	4.8	4.7	4.3
			10.0	6.2	6.0	5.8	5.7	6.0	5.8	5.7	5.5	5.6	5.5	5.4	5.2	5.3	5.2	5.1	4.9	4.5

