

# 屋内照明器具特性

|         |                    |  |  |  |  |           |  |  |  |  |
|---------|--------------------|--|--|--|--|-----------|--|--|--|--|
| 品番 (品名) | XF X4 5 9 KUW      |  |  |  |  |           |  |  |  |  |
| 光源      | LED4000_85_4850 x1 |  |  |  |  | 4850.0 lm |  |  |  |  |
| 管理番号    | K0192151(0)D 1     |  |  |  |  |           |  |  |  |  |
| BZ分類    | BZ5/2.8/BZ4        |  |  |  |  |           |  |  |  |  |

|        |         |                 |                  |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    |    |    |
|--------|---------|-----------------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|----|----|----|----|----|
| 器具効率   | 100%    | 天井              | 80%              |     |     |     | 70% |     |     |     | 50% |     |    |    | 30% |    |    |    | 0% |    |
|        |         | 壁               | 70               | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10 | 70  | 50 | 30 | 10 | 0% |    |
| 上方光束   | 1%      | 床               | 10%              |     |     |     | 10% |     |     |     | 10% |     |    |    | 10% |    |    |    | 0% |    |
| 下方光束   | 99%     | 室指数             | 照明率 ( X0.01) ZCM |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    |    |    |
| 保守率    | 良       | 0.81            | 0.6              | 57  | 45  | 37  | 32  | 56  | 44  | 37  | 32  | 53  | 43 | 36 | 31  | 51 | 42 | 36 | 31 | 29 |
|        | 中       | 0.77            | 0.8              | 67  | 56  | 48  | 42  | 66  | 55  | 47  | 42  | 63  | 53 | 47 | 42  | 60 | 52 | 46 | 41 | 39 |
|        | 否       | 0.68            | 1.0              | 74  | 63  | 55  | 50  | 72  | 62  | 55  | 50  | 69  | 61 | 54 | 49  | 66 | 59 | 53 | 49 | 46 |
|        |         |                 | 1.25             | 80  | 70  | 63  | 57  | 78  | 69  | 62  | 57  | 75  | 67 | 61 | 57  | 72 | 66 | 60 | 56 | 54 |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5              | 84  | 75  | 68  | 63  | 82  | 74  | 68  | 63  | 79  | 72 | 67 | 62  | 76 | 70 | 65 | 61 | 59 |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0              | 90  | 82  | 76  | 72  | 88  | 81  | 76  | 71  | 85  | 79 | 74 | 70  | 82 | 77 | 73 | 69 | 67 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5              | 93  | 87  | 82  | 77  | 91  | 86  | 81  | 77  | 88  | 84 | 79 | 76  | 86 | 81 | 78 | 75 | 72 |
|        | 横方向 (A) | 縦方向 (B)         | 3.0              | 96  | 90  | 86  | 82  | 94  | 89  | 85  | 81  | 91  | 87 | 83 | 80  | 88 | 85 | 82 | 79 | 76 |
| 1.5m   | 1.94m   | 2.11m           | 4.0              | 99  | 95  | 91  | 87  | 97  | 93  | 90  | 87  | 94  | 91 | 88 | 85  | 92 | 89 | 86 | 84 |    |
| 2      | 2.56    | 2.66            | 5.0              | 101 | 97  | 94  | 91  | 99  | 96  | 93  | 90  | 96  | 94 | 91 | 89  | 94 | 91 | 89 | 87 |    |
| 2.5    | 3.18    | 3.22            | 7.0              | 103 | 100 | 98  | 96  | 101 | 99  | 97  | 95  | 99  | 97 | 95 | 93  | 96 | 94 | 93 | 91 |    |
| 3      | 3.8     | 3.81            | 10.0             | 104 | 103 | 101 | 99  | 103 | 101 | 100 | 98  | 100 | 99 | 98 | 96  | 98 | 97 | 95 | 94 |    |

