

# 屋内照明器具特性

品番 (品名)	L G W 5 1 7 6 2 W														
光源	LED2700_70_870 ×1 870.0 l m														
管理番号	K0161764 ( 0 ) DB 1														
B Z 分類	B Z 5														

器具効率	76 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	76 %	室指数	照明率 ( X0.01 ) Z C M																	
保守率	良	0.63	0.6	43	34	28	24	42	34	28	24	40	33	28	24	39	32	27	24	22
	中	0.6	0.8	51	42	36	32	50	42	36	32	48	41	35	32	46	40	35	31	30
	否	0.56	1.0	56	48	42	38	55	47	42	37	52	46	41	37	50	45	40	37	35
			1.25	60	53	48	43	59	52	47	43	57	51	46	43	55	50	46	42	41
下方投影面積		c m <sup>2</sup>	1.5	63	57	52	47	62	56	51	47	60	55	50	47	58	53	49	46	44
等価発光面積		c m <sup>2</sup>	2.0	68	62	58	54	66	61	57	53	64	60	56	53	62	58	55	52	50
取付高さ	器具間隔最大限		2.5	70	66	62	58	69	65	61	58	67	63	60	57	65	61	59	56	54
	横方向 ( A )	縦方向 ( B )	3.0	72	68	64	61	71	67	64	61	69	65	63	60	67	64	61	59	57
H m	1.24 H m	1.24 H m	4.0	75	71	68	66	73	70	68	65	71	69	66	64	69	67	65	63	61
			5.0	76	73	71	69	75	72	70	68	73	71	69	67	71	69	67	66	64
			7.0	78	76	74	72	77	75	73	71	75	73	71	70	73	71	70	69	67
			10.0	79	78	76	75	78	77	75	74	76	75	74	73	74	73	72	71	69

