

屋内照明器具特性

品番 (品名)	L G W 5 1 7 7 0 B				
光源	LED5000_70_530 x1		530.0 l m		
管理番号	K0161768 (0) DB 1				
B Z 分類	B Z 5				

器具効率	66 %	天井	80 %				70 %				50 %				30 %				0 %			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
		床	10 %				10 %				10 %				10 %				0 %			
上方光束	0 %	室指数																				
下方光束	66 %	照明率 (X 0.01)																				
		Z C M																				
保守率	良 中 否	0.63	0.6	0.56	0.6	3.8	3.0	2.5	2.1	3.7	2.9	2.4	2.1	3.5	2.9	2.4	2.1	3.4	2.8	2.4	2.1	1.9
		0.6	0.8	4.4	3.7	3.2	2.8	4.3	3.6	3.1	2.8	4.1	3.5	3.1	2.8	4.0	3.4	3.0	2.7	2.6		
		1.0	4.9	4.2	3.7	3.3	4.8	4.1	3.6	3.3	4.6	4.0	3.6	3.2	4.4	3.9	3.5	3.2	3.1			
		0.56	1.25	5.3	4.6	4.1	3.8	5.1	4.6	4.1	3.8	4.9	4.4	4.0	3.7	4.8	4.3	4.0	3.7	3.5		
下方投影面積			c m ²		1.5	5.5	4.9	4.5	4.1	5.4	4.9	4.5	4.1	5.2	4.8	4.4	4.1	5.0	4.6	4.3	4.0	3.9
			c m ²		2.0	5.9	5.4	5.0	4.7	5.8	5.3	5.0	4.7	5.6	5.2	4.9	4.6	5.4	5.1	4.8	4.6	4.4
取付高さ	器具間隔最大限				2.5	6.1	5.7	5.4	5.1	6.0	5.6	5.3	5.0	5.8	5.5	5.2	5.0	5.6	5.4	5.1	4.9	4.7
	横方向 (A)	縦方向 (B)			3.0	6.3	5.9	5.6	5.3	6.2	5.9	5.6	5.3	6.0	5.7	5.5	5.2	5.8	5.6	5.4	5.2	5.0
H m	1.24 H m	1.24 H m			4.0	6.5	6.2	6.0	5.7	6.4	6.1	5.9	5.7	6.2	6.0	5.8	5.6	6.0	5.8	5.7	5.5	5.3
					5.0	6.6	6.4	6.2	6.0	6.5	6.3	6.1	5.9	6.3	6.2	6.0	5.8	6.2	6.0	5.9	5.7	5.5
					7.0	6.8	6.6	6.4	6.3	6.7	6.5	6.4	6.2	6.5	6.4	6.2	6.1	6.3	6.2	6.1	6.0	5.8
					10.0	6.9	6.7	6.6	6.5	6.8	6.7	6.6	6.4	6.6	6.5	6.4	6.3	6.5	6.4	6.3	6.2	6.0

