

# 屋内照明器具特性

品番 (品名)	LGCX58101									
光源	LED6200_70_5499 x1 5499.0lm									
管理番号	K0164401(0)D 1									
BZ分類	BZ6/1.1/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束		29%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
	下方光束		71%		10%				10%				10%				10%				0%		
室指数	照明率 ( X0.01 ) ZCM																						
保守率	良	0.63	0.6	0.6	0.56	0.6	50	38	30	25	48	36	29	24	42	33	27	22	38	30	25	21	17
	中	0.6	0.6	0.6	0.6	0.8	60	48	40	34	56	46	38	33	50	42	35	31	45	38	32	28	24
	否	0.56	0.56	0.56	0.56	1.0	66	55	47	41	62	52	45	40	56	48	42	37	50	43	38	34	28
						1.25	72	62	54	48	68	59	52	46	61	53	48	43	54	48	44	40	33
下方投影面積			cm <sup>2</sup>		1.5	76	67	59	54	72	64	57	52	64	58	52	48	58	52	48	44	37	
			cm <sup>2</sup>		2.0	82	74	67	62	77	70	64	60	70	64	59	55	62	58	54	51	43	
取付高さ	器具間隔最大限				2.5	85	78	73	68	81	75	70	65	73	68	64	60	65	62	58	55	47	
	横方向 (A)		縦方向 (B)		3.0	88	82	76	72	83	78	73	69	75	71	67	64	68	64	61	58	50	
Hm	1.35Hm	1.35Hm	1.35Hm	1.35Hm	4.0	91	86	82	78	87	82	78	75	78	75	72	69	71	68	65	63	54	
					5.0	93	89	85	82	89	85	82	79	80	77	75	72	73	70	68	66	57	
					7.0	95	92	89	87	91	88	86	83	83	81	78	76	75	73	71	70	60	
					10.0	97	95	93	91	93	91	89	87	85	83	81	80	77	75	74	73	63	

