

# 屋内照明器具特性

品番 (品名)	L G W 8 0 3 2 6														
光源	LED5000_70_382 x1 382.0 l m														
管理番号	K0160244 ( 0 ) DR 1														
B Z 分類	B Z 9														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	50 %	室指数	照明率 ( X 0.01 )															Z C M			
下方光束	50 %																				
保守率	良 中 否 0.63 0.6 0.56	0.6	4.4	3.2	2.4	1.8	4.0	2.9	2.2	1.7	3.3	2.4	1.8	1.4	2.6	1.9	1.4	1.1	0.6		
		0.8	5.2	4.0	3.2	2.5	4.8	3.7	2.9	2.3	3.9	3.0	2.4	2.0	3.1	2.5	2.0	1.6	0.9		
		1.0	5.8	4.6	3.8	3.1	5.3	4.3	3.5	2.9	4.4	3.5	2.9	2.4	3.5	2.8	2.4	2.0	1.2		
		1.25	6.4	5.3	4.4	3.8	5.8	4.8	4.1	3.5	4.8	4.0	3.4	2.9	3.8	3.2	2.8	2.4	1.5		
下方投影面積	c m <sup>2</sup>	1.5	6.8	5.7	4.9	4.3	6.2	5.3	4.6	4.0	5.1	4.4	3.8	3.3	4.1	3.6	3.1	2.7	1.7		
		2.0	7.4	6.4	5.7	5.1	6.7	5.9	5.3	4.7	5.6	5.0	4.4	4.0	4.5	4.0	3.6	3.3	2.1		
取付高さ	器具間隔最大限		2.5	7.7	6.9	6.2	5.6	7.1	6.4	5.8	5.2	5.9	5.3	4.9	4.4	4.8	4.4	4.0	3.7	2.4	
	横方向 ( A )	縦方向 ( B )	3.0	8.0	7.3	6.6	6.1	7.4	6.7	6.1	5.7	6.1	5.6	5.2	4.8	5.0	4.6	4.3	4.0	2.7	
H m	1.88 H m	1.63 H m	4.0	8.3	7.7	7.2	6.7	7.7	7.2	6.7	6.2	6.5	6.0	5.7	5.3	5.3	5.0	4.7	4.4	3.0	
			5.0	8.6	8.1	7.6	7.2	7.9	7.5	7.0	6.6	6.7	6.3	6.0	5.7	5.5	5.2	5.0	4.7	4.3	3.3
			7.0	8.9	8.4	8.1	7.7	8.2	7.8	7.5	7.2	6.9	6.7	6.4	6.1	5.7	5.5	5.3	5.1	3.6	
			10.0	9.1	8.8	8.5	8.2	8.4	8.1	7.9	7.6	7.2	6.9	6.7	6.5	6.0	5.8	5.6	5.5	3.9	

