

# 屋内照明器具特性

品番 (品名)	L G W 8 5 0 3 0 W K															
光源	LDA5 L - H / E / W × 1                      4 8 5 . 0 1 m															
管理番号	K 0 1 6 2 7 9 2 ( 0 ) D Y 1															
B Z 分類	B Z 4															

器具効率	37 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 ( X 0 . 0 1 )																Z C M		
下方光束	37 %																				
保守率	良 中 否 0.63 0.6 0.56	0.6	2.2	1.7	1.5	1.3	2.1	1.7	1.5	1.3	2.0	1.7	1.4	1.3	2.0	1.6	1.4	1.3	1.2		
		0.8	2.5	2.1	1.9	1.7	2.5	2.1	1.9	1.7	2.4	2.1	1.8	1.7	2.3	2.0	1.8	1.6	1.6		
		1.0	2.8	2.4	2.1	1.9	2.7	2.4	2.1	1.9	2.6	2.3	2.1	1.9	2.5	2.3	2.1	1.9	1.8		
		1.25	3.0	2.7	2.4	2.2	2.9	2.6	2.4	2.2	2.8	2.6	2.4	2.2	2.7	2.5	2.3	2.2	2.1		
下方投影面積	c m <sup>2</sup>	1.5	3.1	2.8	2.6	2.4	3.1	2.8	2.6	2.4	3.0	2.7	2.6	2.4	2.9	2.7	2.5	2.4	2.3		
		2.0	3.3	3.1	2.9	2.7	3.3	3.1	2.9	2.7	3.2	3.0	2.8	2.7	3.1	2.9	2.8	2.7	2.6		
取付高さ	器具間隔最大限		2.5	3.5	3.3	3.1	2.9	3.4	3.2	3.1	2.9	3.3	3.1	3.0	2.9	3.2	3.1	2.9	2.8	2.8	
	横方向 (A)	縦方向 (B)	3.0	3.5	3.4	3.2	3.1	3.5	3.3	3.2	3.1	3.4	3.2	3.1	3.0	3.3	3.2	3.1	3.0	2.9	
H m	1.18 H m	1.19 H m	4.0	3.7	3.5	3.4	3.3	3.6	3.5	3.4	3.2	3.5	3.4	3.3	3.2	3.4	3.3	3.2	3.1	3.1	
			5.0	3.7	3.6	3.5	3.4	3.7	3.6	3.5	3.4	3.6	3.5	3.4	3.3	3.5	3.4	3.3	3.2	3.2	
			7.0	3.8	3.7	3.6	3.6	3.7	3.7	3.6	3.5	3.6	3.6	3.5	3.5	3.6	3.5	3.5	3.4	3.3	
			10.0	3.8	3.8	3.7	3.7	3.8	3.7	3.7	3.6	3.7	3.7	3.6	3.6	3.6	3.6	3.5	3.5	3.4	

