

# 屋内照明器具特性

品番 (品名)	L G W 8 5 2 3 6 S														
光源	LED3500_70_870 x1 870.0 l m														
管理番号	K0161776 ( 0 ) DB 1														
B Z 分類	B Z 5														

器具効率	55 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	4 %																			
下方光束	51 %																			
室指数	照明率 ( X 0.01 ) Z C M																			
保守率	良 中 否	0.63	0.6	3.0	2.3	1.9	1.6	2.9	2.3	1.9	1.6	2.7	2.2	1.8	1.5	2.6	2.1	1.8	1.5	1.4
		0.6	0.8	3.5	2.9	2.5	2.1	3.4	2.8	2.4	2.1	3.2	2.7	2.3	2.1	3.0	2.6	2.3	2.0	1.9
		0.56	1.0	3.9	3.3	2.9	2.5	3.8	3.2	2.8	2.5	3.6	3.1	2.7	2.4	3.4	2.9	2.6	2.4	2.2
			1.25	4.2	3.7	3.2	2.9	4.1	3.6	3.2	2.9	3.9	3.4	3.1	2.8	3.6	3.3	3.0	2.7	2.6
下方投影面積		c m <sup>2</sup>																		
等価発光面積		c m <sup>2</sup>																		
取付高さ	器具間隔最大限		2.5	4.9	4.6	4.3	4.0	4.8	4.5	4.2	3.9	4.6	4.3	4.0	3.8	4.3	4.1	3.9	3.7	3.5
	横方向 ( A )	縦方向 ( B )	3.0	5.1	4.8	4.5	4.2	5.0	4.6	4.4	4.2	4.7	4.5	4.2	4.0	4.5	4.3	4.1	3.9	3.7
H m	1.26 H m	1.26 H m	4.0	5.3	5.0	4.8	4.5	5.1	4.9	4.7	4.5	4.9	4.7	4.5	4.3	4.7	4.5	4.3	4.2	3.9
			5.0	5.4	5.1	4.9	4.8	5.2	5.0	4.8	4.7	5.0	4.8	4.7	4.5	4.8	4.6	4.5	4.4	4.1
			7.0	5.5	5.3	5.2	5.0	5.4	5.2	5.1	4.9	5.1	5.0	4.9	4.8	4.9	4.8	4.7	4.6	4.3
			10.0	5.6	5.5	5.4	5.2	5.5	5.4	5.3	5.1	5.3	5.2	5.1	5.0	5.0	4.9	4.9	4.8	4.5

