

屋内照明器具特性

品番 (品名)	L G W 8 5 2 3 7 Y									
光源	LED2700_70_870 x1					870.0 l m				
管理番号	K0161776 (0) DB 1									
B Z 分類	B Z 5									

器具効率	55 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	4 %	室指数																	照明率 (X0.01)																	Z C M																
下方光束	51 %																																																			
保守率	良 中 否	0.63	0.6	0.56	0.6	30	23	19	16	29	23	19	16	27	22	18	15	26	21	18	15	14																														
		0.6	0.8	3.5	2.9	2.5	2.1	3.4	2.8	2.4	2.1	3.2	2.7	2.3	2.1	3.0	2.6	2.3	2.0	1.9																																
		1.0	3.9	3.3	2.9	2.5	3.8	3.2	2.8	2.5	3.6	3.1	2.7	2.4	3.4	2.9	2.6	2.4	2.2																																	
		0.56	1.25	4.2	3.7	3.2	2.9	4.1	3.6	3.2	2.9	3.9	3.4	3.1	2.8	3.6	3.3	3.0	2.7	2.6																																
下方投影面積	c m ²	1.5	4.4	3.9	3.5	3.2	4.3	3.8	3.5	3.2	4.1	3.7	3.4	3.1	3.9	3.5	3.2	3.0	2.8																																	
		2.0	4.8	4.3	4.0	3.7	4.6	4.2	3.9	3.6	4.4	4.0	3.8	3.5	4.1	3.9	3.6	3.4	3.2																																	
取付高さ	器具間隔最大限		2.5	4.9	4.6	4.3	4.0	4.8	4.5	4.2	3.9	4.6	4.3	4.0	3.8	4.3	4.1	3.9	3.7	3.5																																
	横方向 (A)	縦方向 (B)	3.0	5.1	4.8	4.5	4.2	5.0	4.6	4.4	4.2	4.7	4.5	4.2	4.0	4.5	4.3	4.1	3.9	3.7																																
H m	1.26 H m	1.26 H m	4.0	5.3	5.0	4.8	4.5	5.1	4.9	4.7	4.5	4.9	4.7	4.5	4.3	4.7	4.5	4.3	4.2	3.9																																
			5.0	5.4	5.1	4.9	4.8	5.2	5.0	4.8	4.7	5.0	4.8	4.7	4.5	4.8	4.6	4.5	4.4	4.1																																
			7.0	5.5	5.3	5.2	5.0	5.4	5.2	5.1	4.9	5.1	5.0	4.9	4.8	4.9	4.8	4.7	4.6	4.3																																
			10.0	5.6	5.5	5.4	5.2	5.5	5.4	5.3	5.1	5.3	5.2	5.1	5.0	5.0	4.9	4.9	4.8	4.5																																

