

屋内照明器具特性

品番 (品名)	LGW85030YK	
光源	LDA5L-H/E/W ×1	485.0 lm
管理番号	K0162792(0)DY1	
BZ分類	BZ4	

器具効率	37%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	37%	室指数	照明率 (×0.01)																ZCM	
保守率	良	0.63	0.6	2.2	1.7	1.5	1.3	2.1	1.7	1.5	1.3	2.0	1.7	1.4	1.3	2.0	1.6	1.4	1.3	1.2
	中	0.6	0.8	2.5	2.1	1.9	1.7	2.5	2.1	1.9	1.7	2.4	2.1	1.8	1.7	2.3	2.0	1.8	1.6	1.6
	否	0.56	1.0	2.8	2.4	2.1	1.9	2.7	2.4	2.1	1.9	2.6	2.3	2.1	1.9	2.5	2.3	2.1	1.9	1.8
			1.25	3.0	2.7	2.4	2.2	2.9	2.6	2.4	2.2	2.8	2.6	2.4	2.2	2.7	2.5	2.3	2.2	2.1
下方投影面積		cm ²	1.5	3.1	2.8	2.6	2.4	3.1	2.8	2.6	2.4	3.0	2.7	2.6	2.4	2.9	2.7	2.5	2.4	2.3
等価発光面積		cm ²	2.0	3.3	3.1	2.9	2.7	3.3	3.1	2.9	2.7	3.2	3.0	2.8	2.7	3.1	2.9	2.8	2.7	2.6
取付高さ	器具間隔最大限		2.5	3.5	3.3	3.1	2.9	3.4	3.2	3.1	2.9	3.3	3.1	3.0	2.9	3.2	3.1	2.9	2.8	2.8
	横方向 (A)	縦方向 (B)	3.0	3.5	3.4	3.2	3.1	3.5	3.3	3.2	3.1	3.4	3.2	3.1	3.0	3.3	3.2	3.1	3.0	2.9
Hm	1.18Hm	1.19Hm	4.0	3.7	3.5	3.4	3.3	3.6	3.5	3.4	3.2	3.5	3.4	3.3	3.2	3.4	3.3	3.2	3.2	3.1
			5.0	3.7	3.6	3.5	3.4	3.7	3.6	3.5	3.4	3.6	3.5	3.4	3.3	3.5	3.4	3.3	3.3	3.2
			7.0	3.8	3.7	3.6	3.6	3.7	3.7	3.6	3.5	3.6	3.6	3.5	3.5	3.6	3.5	3.5	3.4	3.3
			10.0	3.8	3.8	3.7	3.7	3.8	3.7	3.7	3.6	3.7	3.7	3.6	3.6	3.6	3.6	3.5	3.5	3.4

