

屋内照明器具特性	
品番 (品名)	LGW85241B
光源	LED3500_70_530 x1 530.0 l m
管理番号	K0161779(0)DB1
BZ分類	BZ5

器具効率	49 %	天井	80 %				70 %				50 %				30 %				0 %																			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																			
		床	10 %				10 %				10 %				10 %				0 %																			
上方光束	3 %	室指数																		照明率 ( X0.01 )																		ZCM
下方光束	46 %																																					
保守率	良 中 否 0.63 0.6 0.56	0.6	27	21	17	14	26	20	17	14	25	20	16	14	23	19	16	14	12																			
		0.8	32	26	22	19	31	25	22	19	29	24	21	19	27	23	20	18	17																			
		1.0	35	30	26	23	34	29	25	22	32	28	24	22	30	26	24	21	20																			
		1.25	38	33	29	26	37	32	29	26	35	31	28	25	33	29	27	25	23																			
下方投影面積	c m <sup>2</sup>	1.5	40	35	32	29	39	35	31	29	37	33	30	28	35	32	29	27	25																			
		2.0	43	39	36	33	41	38	35	32	39	36	34	32	37	35	33	31	29																			
取付高さ	器具間隔最大限		2.5	44	41	38	36	43	40	37	35	41	38	36	34	39	37	35	33																			
	横方向 (A)	縦方向 (B)	3.0	46	43	40	38	44	42	39	37	42	40	38	36	40	38	37	35																			
H m	1.27 H m	1.27 H m	4.0	47	45	43	41	46	44	42	40	44	42	40	39	42	40	39	38																			
			5.0	48	46	44	43	47	45	43	42	45	43	42	41	43	42	40	39	37																		
			7.0	49	48	46	45	48	47	45	44	46	45	44	43	44	43	42	41																			
			10.0	50	49	48	47	49	48	47	46	47	46	45	45	44	44	43	41																			

