

屋内照明器具特性

品番 (品名)	L G W 8 5 2 1 0 Z															
光源	LDA4 L - H - E17 / E / S / W / 2 x1 440.0 1 m															
管理番号	K0140574 (0) DB 1															
B Z 分類	B Z 1 0															

器具効率	87 %	天井	80 %				70 %				50 %				30 %				0 %						
	上方光束		76 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
	下方光束		11 %	10 %				10 %				10 %				10 %				0 %					
室指数	照明率 (X0.01) ZCM																								
保守率	良	0.63	0.6	0.56	0.6	37	27	21	17	32	24	19	15	23	17	13	11	14	11	8	6	0			
	中	0.6	0.6	0.56	0.6	44	34	28	23	38	30	24	20	27	21	17	14	17	13	11	9	0			
	否	0.56	0.6	0.56	0.6	49	39	33	28	42	34	29	25	30	24	21	18	18	15	13	11	0			
下方投影面積 等価発光面積	c m ² c m ²	1.25	1.5	2.0	2.5	53	44	38	33	46	39	33	29	32	28	24	21	20	17	15	13	1			
		2.5	3.0	4.0	5.0	63	57	53	48	55	50	46	42	40	36	33	31	25	23	21	19	2			
		3.0	4.0	5.0	7.0	65	60	56	52	57	53	49	45	41	38	35	33	26	24	22	21	3			
取付 高さ	器具間隔最大限		H m	0.00 H m	0.00 H m	4.0	5.0	7.0	10.0	68	64	60	56	61	58	55	52	44	42	40	38	27	26	24	23
	5.0	7.0				10.0	70	66	63	60	61	58	55	52	44	42	40	38	28	27	26	24			
	7.0	10.0				72	69	66	64	63	60	58	56	46	44	42	41	30	29	27	26				
						7.0	10.0	72	69	66	64	63	60	58	56	46	44	42	41	30	29	27	26		
						10.0	73	71	69	67	64	63	61	59	47	46	45	43	31	30	29	28			

