

屋内照明器具特性

品番 (品名)	L G W 8 5 2 3 0 S	
光源	LED5000_70_870 ×1	870.0 l m
管理番号	K0161778 (0) DB 1	
B Z 分類	B Z 5	

器具効率	55 %	天井	80 %				70 %				50 %				30 %				0 %			
	上方光束 4 %		反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
下方光束 51 %	室指数	照明率 (X 0.01)																				Z C M
保守率	良 中 否	0.63	0.6	30	23	19	16	29	23	19	16	27	22	18	16	26	21	18	15	14		
		0.6	0.8	35	29	25	21	34	28	24	21	32	27	23	21	30	26	23	20	19		
		0.56	1.0	39	33	29	25	38	32	28	25	36	31	27	24	34	29	26	24	22		
			1.25	42	37	32	29	41	36	32	29	39	34	31	28	36	33	30	27	26		
下方投影面積	c m ²		1.5	44	39	35	32	43	38	35	32	41	37	34	31	38	35	32	30	28		
	等価発光面積		c m ²	2.0	47	43	40	37	46	42	39	36	44	40	38	35	41	39	36	34	32	
取付高さ	器具間隔最大限		2.5	49	46	43	40	48	45	42	39	46	43	40	38	43	41	39	37	35		
	横方向 (A)	縦方向 (B)	3.0	51	47	45	42	49	46	44	42	47	44	42	40	45	43	41	39	37		
H m	1.27 H m	1.27 H m	4.0	53	50	48	45	51	49	47	45	49	47	45	43	46	45	43	42	39		
			5.0	54	51	49	48	52	50	48	47	50	48	47	45	48	46	45	44	41		
			7.0	55	53	52	50	54	52	51	49	51	50	49	48	49	48	47	46	43		
			10.0	56	55	53	52	55	54	52	51	52	51	50	50	50	49	49	48	45		

