

# 屋内照明器具特性

品番 (品名)	L G W 8 5 2 3 1 B														
光源	LED3500_70_870 x1 870.0 l m														
管理番号	K0161778 ( 0 ) DB 1														
B Z 分類	B Z 5														

器具効率	55 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	4 %																			
下方光束	51 %																			
室指数	照明率 ( X 0.01 ) Z C M																			
保守率	良 0.63 中 0.6 否 0.56	0.6	30	23	19	16	29	23	19	16	27	22	18	16	26	21	18	15	14	
		0.8	35	29	25	21	34	28	24	21	32	27	23	21	30	26	23	20	19	
		1.0	39	33	29	25	38	32	28	25	36	31	27	24	34	29	26	24	22	
		1.25	42	37	32	29	41	36	32	29	39	34	31	28	36	33	30	27	26	
下方投影面積	c m <sup>2</sup>	1.5	44	39	35	32	43	38	35	32	41	37	34	31	38	35	32	30	28	
		2.0	47	43	40	37	46	42	39	36	44	40	38	35	41	39	36	34	32	
取付高さ	器具間隔最大限		2.5	49	46	43	40	48	45	42	39	46	43	40	38	43	41	39	37	35
	横方向 ( A )	縦方向 ( B )	3.0	51	47	45	42	49	46	44	42	47	44	42	40	45	43	41	39	37
H m	1.27 H m	1.27 H m	4.0	53	50	48	45	51	49	47	45	49	47	45	43	46	45	43	42	39
			5.0	54	51	49	48	52	50	48	47	50	48	47	45	48	46	45	44	41
			7.0	55	53	52	50	54	52	51	49	51	50	49	48	49	48	47	46	43
			10.0	56	55	53	52	55	54	52	51	52	51	50	50	50	49	49	48	45

