

屋内照明器具特性	
品番 (品名)	LGW85240B
光源	LED5000_70_530 x1 530.0 l m
管理番号	K0161779(0)DB1
BZ分類	BZ5

器具効率	49 %	天井	80 %				70 %				50 %				30 %				0 %																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																				
		床	10 %				10 %				10 %				10 %				0 %																																				
上方光束	3 %	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	46 %																																																						
保守率	良 0.63 中 0.6 否 0.56	0.6	2.7	2.1	1.7	1.4	2.6	2.0	1.7	1.4	2.5	2.0	1.6	1.4	2.3	1.9	1.6	1.4	1.2																																				
		0.8	3.2	2.6	2.2	1.9	3.1	2.5	2.2	1.9	2.9	2.4	2.1	1.9	2.7	2.3	2.0	1.8	1.7																																				
		1.0	3.5	3.0	2.6	2.3	3.4	2.9	2.5	2.2	3.2	2.8	2.4	2.2	3.0	2.6	2.4	2.1	2.0																																				
		1.25	3.8	3.3	2.9	2.6	3.7	3.2	2.9	2.6	3.5	3.1	2.8	2.5	3.3	2.9	2.7	2.5	2.3																																				
下方投影面積	c m ²	1.5	4.0	3.5	3.2	2.9	3.9	3.5	3.1	2.9	3.7	3.3	3.0	2.8	3.5	3.2	2.9	2.7	2.5																																				
		2.0	4.3	3.9	3.6	3.3	4.1	3.8	3.5	3.2	3.9	3.6	3.4	3.2	3.7	3.5	3.3	3.1	2.9																																				
取付高さ	器具間隔最大限		2.5	4.4	4.1	3.8	3.6	4.3	4.0	3.7	3.5	4.1	3.8	3.6	3.4	3.9	3.7	3.5	3.3																																				
	横方向 (A)	縦方向 (B)	3.0	4.6	4.3	4.0	3.8	4.4	4.2	3.9	3.7	4.2	4.0	3.8	3.6	4.0	3.8	3.7	3.5	3.3																																			
H m	1.27 H m	1.27 H m	4.0	4.7	4.5	4.3	4.1	4.6	4.4	4.2	4.0	4.4	4.2	4.0	3.9	4.2	4.0	3.9	3.8	3.5																																			
			5.0	4.8	4.6	4.4	4.3	4.7	4.5	4.3	4.2	4.5	4.3	4.2	4.1	4.3	4.2	4.0	3.9	3.7																																			
			7.0	4.9	4.8	4.6	4.5	4.8	4.7	4.5	4.4	4.6	4.5	4.4	4.3	4.4	4.3	4.2	4.1	3.9																																			
			10.0	5.0	4.9	4.8	4.7	4.9	4.8	4.7	4.6	4.7	4.6	4.5	4.5	4.4	4.4	4.3	4.1	3.9																																			

