

屋内照明器具特性	
品番 (品名)	XF X440VJ W
光源	LED4000_85_3200 ×1 3200.0 lm
管理番号	K0193759 (0) DB 1
BZ分類	BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																					
保守率		良 中 否	0 . 8 1	0 . 6	6 1	5 0	4 3	3 8	6 0	4 9	4 2	3 7	5 8	4 8	4 2	3 7	5 6	4 7	4 1	3 7	3 5				
			0 . 7 7	0 . 8	7 1	6 1	5 3	4 8	7 0	6 0	5 3	4 8	6 7	5 9	5 3	4 8	6 5	5 7	5 2	4 8	4 6				
			1 . 0	7 7	6 8	6 1	5 6	7 6	6 7	6 1	5 6	7 3	6 6	6 0	5 5	7 1	6 4	5 9	5 5	5 3					
			0 . 6 8	1 . 2 5	8 3	7 4	6 8	6 3	8 2	7 4	6 7	6 3	7 9	7 2	6 7	6 2	7 6	7 0	6 6	6 2	6 0				
下方投影面積 等価発光面積		c m ²	1 . 5	8 7	7 9	7 3	6 8	8 5	7 8	7 2	6 8	8 2	7 6	7 1	6 7	8 0	7 5	7 0	6 7	6 4					
			c m ²	2 . 0	9 2	8 5	8 0	7 6	9 0	8 4	8 0	7 5	8 8	8 3	7 8	7 5	8 5	8 1	7 7	7 4	7 2				
取付 高さ	器具間隔最大限		2 . 5	9 5	9 0	8 5	8 1	9 4	8 9	8 4	8 1	9 1	8 7	8 3	8 0	8 8	8 5	8 1	7 9	7 6					
	横方向 (A) 縦方向 (B)		3 . 0	9 7	9 3	8 8	8 5	9 6	9 1	8 8	8 4	9 3	8 9	8 6	8 3	9 0	8 7	8 5	8 2	8 0					
1 . 5 m	1 . 8 9 m	2 . 0 8 m	4 . 0	1 0 0	9 6	9 3	9 0	9 9	9 5	9 2	8 9	9 6	9 3	9 0	8 8	9 3	9 1	8 9	8 7	8 4					
2	2 . 5 1	2 . 6 4	5 . 0	1 0 2	9 9	9 6	9 3	1 0 0	9 7	9 5	9 3	9 8	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 7					
2 . 5	3 . 1 2	3 . 2 1	7 . 0	1 0 4	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 5	9 7	9 6	9 4	9 3	9 0					
3	3 . 7 3	3 . 7 9	1 0 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 4	1 0 2	1 0 1	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 3					

