

# 屋内照明器具特性

|         |                       |  |  |  |  |           |  |  |  |  |
|---------|-----------------------|--|--|--|--|-----------|--|--|--|--|
| 品番 (品名) | L G W C 7 1 6 3 0     |  |  |  |  |           |  |  |  |  |
| 光源      | LED2700_70_400 x1     |  |  |  |  | 400.0 l m |  |  |  |  |
| 管理番号    | K0147562 ( 0 ) DB 1   |  |  |  |  |           |  |  |  |  |
| B Z 分類  | B Z 4 / 0 . 7 / B Z 3 |  |  |  |  |           |  |  |  |  |

|        |          |                 |                   |     |     |     |      |     |     |     |      |     |     |    |      |    |    |    |       |    |
|--------|----------|-----------------|-------------------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|----|------|----|----|----|-------|----|
| 器具効率   | 100 %    | 天井              | 80 %              |     |     |     | 70 % |     |     |     | 50 % |     |     |    | 30 % |    |    |    | 0 %   |    |
|        |          | 壁               | 70                | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10 | 70   | 50 | 30 | 10 | 0 %   |    |
| 上方光束   | 0 %      | 床               | 10 %              |     |     |     | 10 % |     |     |     | 10 % |     |     |    | 10 % |    |    |    | 0 %   |    |
| 下方光束   | 100 %    | 室指数             | 照明率 ( X 0 . 0 1 ) |     |     |     |      |     |     |     |      |     |     |    |      |    |    |    | Z C M |    |
| 保守率    | 良        | 0.67            | 0.6               | 61  | 49  | 42  | 37   | 60  | 49  | 42  | 37   | 57  | 48  | 42 | 37   | 55 | 47 | 41 | 37    | 35 |
|        | 中        | 0.63            | 0.8               | 71  | 61  | 54  | 49   | 70  | 60  | 54  | 49   | 67  | 59  | 53 | 48   | 65 | 58 | 52 | 48    | 46 |
|        | 否        | 0.56            | 1.0               | 78  | 69  | 62  | 57   | 77  | 68  | 62  | 57   | 74  | 66  | 61 | 56   | 72 | 65 | 60 | 56    | 54 |
|        |          |                 | 1.25              | 84  | 76  | 69  | 65   | 82  | 75  | 69  | 64   | 80  | 73  | 68 | 64   | 77 | 72 | 67 | 63    | 61 |
| 下方投影面積 |          | cm <sup>2</sup> | 1.5               | 88  | 80  | 75  | 70   | 86  | 79  | 74  | 70   | 84  | 78  | 73 | 69   | 81 | 76 | 72 | 69    | 66 |
| 等価発光面積 |          | cm <sup>2</sup> | 2.0               | 93  | 87  | 82  | 78   | 91  | 86  | 81  | 77   | 89  | 84  | 80 | 77   | 86 | 82 | 79 | 76    | 74 |
| 取付高さ   | 器具間隔最大限  |                 | 2.5               | 96  | 91  | 87  | 83   | 94  | 90  | 86  | 82   | 92  | 88  | 84 | 81   | 89 | 86 | 83 | 80    | 78 |
|        | 横方向 (A)  | 縦方向 (B)         | 3.0               | 98  | 94  | 90  | 87   | 97  | 93  | 89  | 86   | 94  | 90  | 87 | 85   | 91 | 89 | 86 | 84    | 81 |
| H m    | 1.22 H m | 1.22 H m        | 4.0               | 101 | 97  | 94  | 91   | 99  | 96  | 93  | 91   | 97  | 94  | 92 | 89   | 94 | 92 | 90 | 88    | 86 |
|        |          |                 | 5.0               | 102 | 99  | 97  | 94   | 101 | 98  | 96  | 94   | 98  | 96  | 94 | 92   | 96 | 94 | 92 | 91    | 88 |
|        |          |                 | 7.0               | 104 | 102 | 100 | 98   | 103 | 101 | 99  | 97   | 100 | 98  | 97 | 96   | 98 | 96 | 95 | 94    | 91 |
|        |          |                 | 10.0              | 105 | 104 | 102 | 101  | 104 | 102 | 101 | 100  | 101 | 100 | 99 | 98   | 99 | 98 | 97 | 96    | 94 |

