

# 屋内照明器具特性

|         |                   |    |       |    |  |
|---------|-------------------|----|-------|----|--|
| 品番 (品名) | L G W C 7 1 6 3 1 |    |       |    |  |
| 光源      | LED2700_70_355    | x1 | 355.0 | lm |  |
| 管理番号    | K0147556(0)DB1    |    |       |    |  |
| BZ分類    | BZ3/6.0/BZ2       |    |       |    |  |

|        |                 |         |               |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |     |    |
|--------|-----------------|---------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|----|
| 器具効率   | 100%            | 天井      | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |    |    | 0%  |    |
|        | 上方光束<br>0%      |         | 反射率           | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10  | 0% |
| 下方光束   | 100%            | 床       |               | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |    |    |     | 0% |
| 室指数    |                 |         | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    | ZCM |    |
| 保守率    | 良               | 0.67    | 0.6           | 63  | 52  | 45  | 40  | 61  | 51  | 44  | 40  | 59  | 50  | 44  | 40  | 57  | 49 | 44 | 39  | 38 |
|        | 中               | 0.63    | 0.8           | 73  | 63  | 57  | 52  | 72  | 63  | 56  | 52  | 69  | 61  | 56  | 51  | 67  | 60 | 55 | 51  | 49 |
|        | 否               | 0.56    | 1.0           | 80  | 71  | 65  | 60  | 79  | 70  | 65  | 60  | 76  | 69  | 64  | 60  | 74  | 68 | 63 | 59  | 57 |
|        |                 |         | 1.25          | 86  | 78  | 72  | 68  | 84  | 77  | 72  | 68  | 82  | 76  | 71  | 67  | 80  | 74 | 70 | 67  | 65 |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5           | 90  | 83  | 77  | 73  | 88  | 82  | 77  | 73  | 86  | 80  | 76  | 72  | 83  | 79 | 75 | 72  | 70 |
|        | 等価発光面積          |         | 2.0           | 94  | 89  | 84  | 81  | 93  | 88  | 84  | 80  | 90  | 86  | 83  | 79  | 88  | 84 | 81 | 79  | 77 |
| 取付高さ   | 器具間隔最大限         |         | 2.5           | 97  | 93  | 89  | 86  | 96  | 92  | 88  | 85  | 93  | 90  | 87  | 84  | 91  | 88 | 85 | 83  | 81 |
|        | 横方向 (A)         | 縦方向 (B) | 3.0           | 99  | 95  | 92  | 89  | 98  | 94  | 91  | 88  | 95  | 92  | 90  | 87  | 93  | 90 | 88 | 86  | 84 |
| Hm     | 1.21Hm          | 1.21Hm  | 4.0           | 102 | 99  | 96  | 93  | 100 | 97  | 95  | 93  | 98  | 95  | 93  | 91  | 95  | 94 | 92 | 90  | 88 |
|        |                 |         | 5.0           | 103 | 100 | 98  | 96  | 102 | 99  | 97  | 95  | 99  | 97  | 96  | 94  | 97  | 95 | 94 | 92  | 90 |
|        |                 |         | 7.0           | 104 | 103 | 101 | 99  | 103 | 102 | 100 | 99  | 101 | 99  | 98  | 97  | 99  | 97 | 96 | 95  | 93 |
|        |                 |         | 10.0          | 106 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99 | 98 | 97  | 95 |

