

屋内照明器具特性

品番 (品名)	LGC45800														
光源	LED6500_70_4100 x1 4100.0 lm														
管理番号	K0157426(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		13%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		87%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.63	0.6	54	42	34	28	52	41	33	28	48	39	32	27	45	37	31	26	24	
	中	0.6	0.8	63	52	44	38	61	50	43	37	57	48	41	36	53	45	40	35	32	
	否	0.56	1.0	70	59	51	45	67	57	50	44	63	54	48	43	59	51	46	41	38	
			1.25	76	66	58	52	73	64	57	51	68	60	54	49	64	57	52	48	44	
下方投影面積	c m ²		1.5	80	70	63	57	77	68	62	56	72	65	59	54	67	61	57	52	48	
	等価発光面積		c m ²	2.0	85	77	71	66	82	75	69	64	77	71	66	62	72	67	63	60	55
取付高さ	器具間隔最大限		2.5	89	82	76	71	86	80	74	70	81	75	71	67	76	71	68	64	59	
	横方向 (A)	縦方向 (B)	3.0	91	85	80	75	88	83	78	74	83	79	75	71	78	74	71	68	63	
1.5m	1.95m	1.95m	4.0	94	90	85	81	92	87	83	80	86	83	79	76	81	78	76	73	68	
2	2.57	2.57	5.0	96	92	89	85	94	90	87	83	88	85	82	80	83	81	79	76	71	
2.5	3.2	3.2	7.0	99	96	93	90	96	93	91	88	91	89	86	84	86	84	82	80	75	
3	3.74	3.74	10.0	101	98	96	94	98	96	94	92	93	91	89	88	88	87	85	84	78	

