

# 屋内照明器具特性

品番 (品名)	LGBZ3615	
光源	LED6200_70_5200 x1	5200.0lm
管理番号	K0161881(1)D 1	
BZ分類	BZ6/0.7/BZ5	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 3%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	97%	床		10%				10%				10%				10%				0%	
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	54	41	33	27	52	40	32	27	49	39	32	27	47	38	31	26	24	
	中	0.6	0.8	64	52	43	37	62	51	43	37	59	49	42	36	56	47	41	36	34	
	否	0.56	1.0	70	59	51	44	69	58	50	44	65	56	49	44	62	54	48	43	40	
			1.25	76	66	58	52	75	65	57	52	71	63	56	51	68	60	55	50	47	
下方投影面積	c m <sup>2</sup>		1.5	81	71	64	58	79	70	63	57	75	67	61	56	72	65	60	55	52	
	等価発光面積		c m <sup>2</sup>	2.0	87	78	72	66	85	77	71	66	81	74	69	64	77	72	67	63	60
取付高さ	器具間隔最大限		2.5	90	83	77	72	88	82	76	71	85	79	74	70	81	76	72	69	66	
	横方向 (A)	縦方向 (B)	3.0	93	87	81	76	91	85	80	76	87	82	78	74	84	80	76	73	70	
H m	1.42 H m	1.42 H m	4.0	96	91	87	83	94	90	85	82	91	87	83	80	87	84	81	78	75	
			5.0	98	94	90	87	96	93	89	86	93	90	87	84	90	87	84	82	78	
			7.0	101	98	94	92	99	96	93	91	96	93	91	89	92	90	88	86	83	
			10.0	103	100	98	96	101	99	97	95	98	96	94	92	95	93	92	90	86	

