

屋内照明器具特性

品番 (品名)	LGBZ3616															
光源	LED6200_70_5200 x1 5200.0lm															
管理番号	K0161881(1)D1															
BZ分類	BZ6/0.7/BZ5															

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	3%	反射率	床	10%				10%				10%				10%				0%
下方光束	97%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否 0.63 0.6 0.56	0.6	5.4	4.1	3.3	2.7	5.2	4.0	3.2	2.7	4.9	3.9	3.2	2.7	4.7	3.8	3.1	2.6	2.4	
		0.8	6.4	5.2	4.3	3.7	6.2	5.1	4.3	3.7	5.9	4.9	4.2	3.6	5.6	4.7	4.1	3.6	3.4	
		1.0	7.0	5.9	5.1	4.4	6.9	5.8	5.0	4.4	6.5	5.6	4.9	4.4	6.2	5.4	4.8	4.3	4.0	
		1.25	7.6	6.6	5.8	5.2	7.5	6.5	5.7	5.2	7.1	6.3	5.6	5.1	6.8	6.0	5.5	5.0	4.7	
下方投影面積	c m ²	1.5	8.1	7.1	6.4	5.8	7.9	7.0	6.3	5.7	7.5	6.7	6.1	5.6	7.2	6.5	6.0	5.5	5.2	
		2.0	8.7	7.8	7.2	6.6	8.5	7.7	7.1	6.6	8.1	7.4	6.9	6.4	7.7	7.2	6.7	6.3	6.0	
取付高さ	器具間隔最大限		2.5	9.0	8.3	7.7	7.2	8.8	8.2	7.6	7.1	8.5	7.9	7.4	7.0	8.1	7.6	7.2	6.9	6.6
	横方向 (A)	縦方向 (B)	3.0	9.3	8.7	8.1	7.6	9.1	8.5	8.0	7.6	8.7	8.2	7.8	7.4	8.4	8.0	7.6	7.3	7.0
H m	1.42 H m	1.42 H m	4.0	9.6	9.1	8.7	8.3	9.4	9.0	8.5	8.2	9.1	8.7	8.3	8.0	8.7	8.4	8.1	7.8	7.5
			5.0	9.8	9.4	9.0	8.7	9.6	9.3	8.9	8.6	9.3	9.0	8.7	8.4	9.0	8.7	8.4	8.2	7.8
			7.0	10.1	9.8	9.4	9.2	9.9	9.6	9.3	9.1	9.6	9.3	9.1	8.9	9.2	9.0	8.8	8.6	8.3
			10.0	10.3	10.0	9.8	9.6	10.1	9.9	9.7	9.5	9.8	9.6	9.4	9.2	9.5	9.3	9.2	9.0	8.6

