

屋内照明器具特性	
品番 (品名)	X F X 4 6 7 G P N
光源	LED5000_85_6560 ×1 6560.0 lm
管理番号	K0192146 (0) D 1
B Z 分類	B Z 4

器具効率			100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
						壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
						床	10 %				10 %				10 %				10 %				0 %
						照明率 (X0.01) ZCM																	
保守率			良 中 否	0.81	0.6	59	48	40	35	58	47	40	35	56	46	40	35	54	45	39	35	33	
				0.77	0.8	70	59	52	47	68	58	51	46	66	57	51	46	64	56	50	46	44	
				0.68	1.0	77	67	60	55	75	66	60	54	73	65	59	54	70	63	58	54	52	
					1.25	83	74	68	62	81	73	67	62	78	71	66	62	76	70	65	61	59	
下方投影面積			cm ²	1.5	87	79	73	68	85	78	72	68	82	76	71	67	80	75	70	67	64		
				2.0	92	86	80	76	91	85	80	76	88	83	78	75	85	81	77	74	72		
等価発光面積			cm ²	2.5	95	90	85	81	94	89	85	81	91	87	83	80	88	85	82	79	77		
				3.0	97	93	89	85	96	92	88	85	93	90	86	84	91	88	85	83	80		
1.5m		1.9 m	2.12 m	4.0	100	97	93	90	99	95	92	90	96	93	91	88	94	91	89	87	85		
2		2.52	2.66	5.0	102	99	96	94	100	98	95	93	98	96	93	91	95	94	92	90	87		
2.5		3.13	3.23	7.0	104	101	99	98	102	100	98	97	100	98	97	95	97	96	95	93	91		
3		3.74	3.81	10.0	105	104	102	101	104	102	101	100	101	100	99	98	99	98	97	96	93		

