

屋内照明器具特性

品番 (品名)	LGBZ6114										
光源	LED6200_70_3300 x1 3300.0 lm										
管理番号	K0163265 (1) DB1										
BZ分類	BZ4										

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	17%	床	10%				10%				10%				10%				0%	
下方光束	83%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	57	46	38	33	55	44	38	33	51	42	36	32	47	40	35	31	28
	中	0.6	0.8	67	56	49	44	64	55	48	43	60	52	46	42	56	49	44	40	37
	否	0.56	1.0	73	64	57	51	71	62	55	50	66	58	53	49	61	55	51	47	43
			1.25	79	70	64	59	76	68	62	58	71	65	59	55	66	61	57	53	49
下方投影面積			1.5	83	75	69	64	80	73	67	63	75	69	64	60	70	65	61	58	53
			2.0	88	82	76	72	85	79	75	71	80	75	71	68	74	71	67	65	59
取付高さ	器具間隔最大限		2.5	91	86	81	77	88	83	79	76	83	79	75	72	77	74	71	69	63
	横方向 (A)	縦方向 (B)	3.0	94	89	85	81	91	86	83	79	85	81	78	76	80	77	74	72	66
Hm	1.22Hm	1.22Hm	4.0	96	93	89	86	93	90	87	84	88	85	82	80	82	80	78	76	70
			5.0	98	95	92	90	95	92	90	87	89	87	85	83	84	82	80	79	72
			7.0	100	98	96	94	97	95	93	91	91	89	88	87	86	84	83	82	75
			10.0	101	100	98	97	98	97	95	94	93	91	90	89	87	86	85	84	77

