

屋内照明器具特性	
品番 (品名)	LGBZ6210
光源	LED6200_70_3500 x1 3500.0 lm
管理番号	K0163280(1)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	11%	床	10%				10%				10%				10%				0%				
下方光束	89%	室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	5.5	4.2	3.5	2.9	5.3	4.1	3.4	2.9	4.9	3.9	3.3	2.8	4.6	3.8	3.2	2.7	2.5			
	中	0.6	0.8	6.4	5.3	4.5	3.9	6.2	5.1	4.4	3.8	5.8	4.9	4.2	3.7	5.4	4.7	4.1	3.6	3.3			
	否	0.56	1.0	7.1	6.0	5.2	4.6	6.8	5.8	5.1	4.5	6.4	5.5	4.9	4.4	6.0	5.3	4.7	4.3	3.9			
			1.25	7.6	6.6	5.9	5.3	7.4	6.5	5.8	5.2	6.9	6.2	5.6	5.1	6.5	5.9	5.3	4.9	4.6			
下方投影面積	cm <sup>2</sup>		1.5	8.0	7.1	6.4	5.8	7.8	7.0	6.3	5.8	7.3	6.6	6.0	5.6	6.9	6.3	5.8	5.4	5.0			
等価発光面積	cm <sup>2</sup>		2.0	8.6	7.8	7.2	6.7	8.3	7.6	7.0	6.6	7.9	7.3	6.8	6.3	7.4	6.9	6.5	6.1	5.7			
取付高さ	器具間隔最大限		2.5	9.0	8.3	7.7	7.2	8.7	8.1	7.6	7.1	8.2	7.7	7.3	6.9	7.8	7.3	7.0	6.6	6.2			
	横方向 (A)	縦方向 (B)	3.0	9.2	8.6	8.1	7.7	8.9	8.4	7.9	7.5	8.5	8.0	7.6	7.3	8.0	7.6	7.3	7.0	6.5			
1.5m	1.89m	1.9m	4.0	9.5	9.1	8.6	8.3	9.3	8.8	8.5	8.1	8.8	8.4	8.1	7.8	8.3	8.0	7.8	7.5	7.0			
2	2.48	2.5	5.0	9.7	9.3	9.0	8.7	9.5	9.1	8.8	8.5	9.0	8.7	8.4	8.2	8.5	8.3	8.1	7.9	7.3			
2.5	3.1	3.11	7.0	10.0	9.7	9.4	9.1	9.7	9.4	9.2	9.0	9.2	9.0	8.8	8.6	8.8	8.6	8.4	8.3	7.7			
3	3.69	3.72	10.0	10.1	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.4	9.3	9.1	9.0	9.0	8.9	8.7	8.6	8.1			

