

屋内照明器具特性	
品番(品名)	LGW80332K(WALL)
光源	LED5000_70_174 x1 174.0 lm
管理番号	K0160247(0)DR1
BZ分類	BZ10/0.7/BZ9

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	50%	床	10%				10%				10%				10%				0%	
下方光束	50%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	4.4	3.1	2.3	1.7	4.0	2.8	2.1	1.6	3.2	2.3	1.7	1.3	2.6	1.9	1.4	1.0	0.5
	中	0.6	0.8	5.2	3.9	3.1	2.4	4.7	3.6	2.8	2.2	3.8	3.0	2.3	1.8	3.0	2.4	1.9	1.5	0.8
	否	0.56	1.0	5.8	4.5	3.7	3.0	5.2	4.2	3.4	2.8	4.3	3.4	2.8	2.3	3.4	2.7	2.2	1.8	1.0
			1.25	6.3	5.2	4.3	3.6	5.7	4.7	4.0	3.3	4.7	3.9	3.3	2.8	3.7	3.1	2.6	2.2	1.3
下方投影面積		cm ²	1.5	6.7	5.6	4.8	4.1	6.1	5.2	4.4	3.8	5.0	4.3	3.7	3.2	4.0	3.5	3.0	2.6	1.6
等価発光面積		cm ²	2.0	7.3	6.3	5.6	4.9	6.7	5.8	5.1	4.6	5.5	4.9	4.3	3.8	4.4	3.9	3.5	3.1	2.0
取付高さ	器具間隔最大限		2.5	7.7	6.8	6.1	5.5	7.0	6.3	5.7	5.1	5.8	5.3	4.7	4.3	4.7	4.3	3.9	3.5	2.3
	横方向(A)	縦方向(B)	3.0	7.9	7.2	6.5	6.0	7.3	6.6	6.0	5.5	6.1	5.5	5.1	4.7	4.9	4.5	4.2	3.8	2.5
Hm	0.00Hm	0.00Hm	4.0	8.3	7.7	7.1	6.6	7.6	7.1	6.6	6.1	6.4	6.0	5.6	5.2	5.2	4.9	4.6	4.3	2.9
			5.0	8.5	8.0	7.5	7.0	7.9	7.4	6.9	6.5	6.6	6.2	5.9	5.6	5.4	5.1	4.9	4.6	3.2
			7.0	8.8	8.4	8.0	7.6	8.2	7.8	7.4	7.1	6.9	6.6	6.3	6.0	5.7	5.5	5.2	5.0	3.5
			10.0	9.0	8.7	8.4	8.1	8.4	8.1	7.8	7.6	7.1	6.9	6.7	6.5	5.9	5.7	5.6	5.4	3.8

