

屋内照明器具特性	
品番 (品名)	X F X 4 3 0 B S N
光源	LED5000_85_2900 ×1 2900.0 lm
管理番号	K0194828 (0) DR 1
B Z 分類	B Z 6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.81	0.6	52	39	31	25	50	38	30	25	46	36	29	24	42	34	28	23	20
			0.77	0.8	61	49	41	35	59	48	40	34	55	45	38	33	50	42	36	32	28
			0.68	1.0	68	56	48	42	65	55	47	41	60	51	45	40	56	48	43	38	34
				1.25	74	63	55	49	71	61	54	48	66	58	51	46	61	54	49	44	40
下方投影面積		cm ²		1.5	78	68	60	54	75	66	59	53	70	62	56	51	65	58	53	49	44
			等価発光面積	cm ²	2.0	84	75	68	63	81	73	67	61	75	69	63	59	70	65	60	56
取付 高さ	器具間隔最大限			2.5	87	80	74	68	84	77	72	67	79	73	68	64	73	69	65	61	56
	横方向 (A)	縦方向 (B)		3.0	90	83	78	73	87	81	76	71	81	76	72	68	76	72	68	65	59
1.5m	1.64 m	2.11 m		4.0	93	88	83	79	90	85	81	77	85	80	77	73	79	76	73	70	64
2	2.18	2.65		5.0	95	91	87	83	92	88	84	81	87	83	80	77	81	79	76	74	67
2.5	2.71	3.21		7.0	98	94	91	88	95	92	89	86	89	87	84	82	84	82	80	78	72
3	3.24	3.78		10.0	100	97	95	92	97	94	92	90	91	89	87	86	86	85	83	81	75

